

U.S. Geological Survey National
Computer Technology Meeting:
Program and Abstracts,
New Orleans, Louisiana,
April 10-15, 1994

NCTM '94



New Orleans, Louisiana

U.S. Geological Survey

Report Documentation Page				Form Approved OMB No. 0704-0188	
Public reporting burden for the collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to a penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number.					
1. REPORT DATE 1994		2. REPORT TYPE N/A		3. DATES COVERED -	
4. TITLE AND SUBTITLE U.S. Geological Survey National Computer Technology Meeting: Program and Abstracts, New Orleans, Louisiana, April 10-15, 1994				5a. CONTRACT NUMBER	
				5b. GRANT NUMBER	
				5c. PROGRAM ELEMENT NUMBER	
6. AUTHOR(S)				5d. PROJECT NUMBER	
				5e. TASK NUMBER	
				5f. WORK UNIT NUMBER	
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) U.S. Department of the Interior 1849 C Street, NW Washington, DC 20240				8. PERFORMING ORGANIZATION REPORT NUMBER	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)				10. SPONSOR/MONITOR'S ACRONYM(S)	
				11. SPONSOR/MONITOR'S REPORT NUMBER(S)	
12. DISTRIBUTION/AVAILABILITY STATEMENT Approved for public release, distribution unlimited					
13. SUPPLEMENTARY NOTES					
14. ABSTRACT					
15. SUBJECT TERMS					
16. SECURITY CLASSIFICATION OF:			17. LIMITATION OF ABSTRACT SAR	18. NUMBER OF PAGES 74	19a. NAME OF RESPONSIBLE PERSON
a. REPORT unclassified	b. ABSTRACT unclassified	c. THIS PAGE unclassified			

U.S. Geological Survey National Computer
Technology Meeting: Program and Abstracts,
New Orleans, Louisiana,
April 10-15, 1994

Compiled by BARBARA H. BALTHROP *and* EVA G. BAKER

U.S. Geological Survey

Open-File Report 94-52

Nashville, Tennessee

1994

U.S. DEPARTMENT OF THE INTERIOR
BRUCE BABBITT, Secretary

U.S. GEOLOGICAL SURVEY
ROBERT M. HIRSCH, Acting Director



Any use of trade, product, or firm name in this report is for identification purposes only and does not constitute endorsement by the U.S. Geological Survey.

For additional information write to:

District Chief
U.S. Geological Survey
810 Broadway, Suite 500
Nashville, Tennessee 37203

Copies of this report may be purchased from:

U.S. Geological Survey
Earth Science Information Center
Open-File Reports Section
Box 25286, MS 517
Denver Federal Center
Denver, Colorado 80225

FOREWORD

The Distributed Information System-II (DIS-II) is actively in use in the U.S. Geological Survey (USGS) to support the USGS mission of providing the hydrologic information and understanding needed for the optimum use and management of the Nation's water resources. Initial plans are being made for augmenting DIS-II with new procurements for additional hardware and software to maintain state-of-the-art computer technology to support our mission. The 7th National Computer Technology Meeting (NCTM '94), which was held in New Orleans, Louisiana, in April 1994, included presentations on the current use of DIS-II hardware and software to solve scientific, administrative, and management problems. NCTM '94 also provided a forum for identifying additional immediate and future needs for enhancements in hardware and software to continue to meet the USGS mission.

This report contains abstracts of technical papers and demonstrations of newly developed software running in the DIS-II computing environment that were presented at the NCTM '94 meeting. Several panel discussions at the meeting provided an exchange of information on issues concerning the use of Internet for scientific purposes, the administration of a relational data base system in support of the hydrologic and administrative data bases, and the use of a paperless report process.

Training continued to be a major part of the NCTM '94. Short courses in system administration, programming languages, network use and analysis, computer security, application software, and data-base techniques were conducted.

Colleen A. Babcock
Technical Coordinator

CONTENTS

	Page
Foreword	iii
Program listing	ix
Demonstration of a digital compact disc containing Navajo and Hopi Indian Reservation data for use in schools to teach remote sensing	
A.V. Acosta	1
Managing relational data bases using Ingres	
D.A. Beeler and M.J. O'Connor	2
Administering Internet Network News (INN), the Netnews server	
D.R. Boldt	3
Telecommunications infrastructure of the U.S. Geological Survey	
R.J. Bonugli	4
Developing graphical applications using a very-high-level language	
Eric Bouck	5
Implementation of the Administrative Information System, first release, in the Water Resources Division, U.S. Geological Survey—results and recommendations	
S.J. Brady, P.G. Clark, W.J. Kratz, and A.A. Sabatini	6
Software development for remote entry of water-use data	
M.R. Bryant and T.W. Holland	7
Parallel virtual machine: capturing the cycles	
L.M. Burgess, Margaret Johnson, and Pearl Wang	8
Design and use of the data report subsystem of the U.S. Geological Survey National Water Information System-II	
S.J. Cauller, D.A. Beeler, C.R. Baxter, and T.E. McKallip	9
Automatic editing and graphical postprocessing of output from the <u>MOD</u> ular <u>F</u> inite <u>E</u> lement (MODFE) model	
J.B. Czarnecki	10
Development of a 14-digit hydrologic coding scheme and boundary data set for New Jersey	
W.H. Ellis, Jr., and C.V. Price	11
Generation of digital base maps for preparation of thematic maps	
C.J. Freitag	12
A vendor-independent fourth-generation language for data manipulation and analysis	
J.L. Fulton	13
The U.S. Geological Survey data base for U.S. Department of Defense Environmental Contamination projects	
C.N. Gerlitz and E.M. Morrell	14
The hydrologic models summary (HYMS): making software information accessible through the Wide Area Information Servers (WAIS) software	
M.Y. Gozé	15
Interoperability of computer systems with dissimilar architecture: a case study	
J.W. Griffin	16
The effect of data generalization on the prediction of hydrologic response	
C.A. Hallam	17
Overview of the paperless report project of the U.S. Geological Survey	
R.M. Hathaway and T.A. Reinitz	18
Computer-based, three-dimensional visualization of observed solute distributions during the Cape Cod tracer test, Massachusetts	
K.M. Hess, M.H. Kruger, E.J. Stock-Alvarez, and D.R. LeBlanc	19
Using a geographic information system to derive urban land use from population data	
K.J. Hitt	20

A site verification program using ARC/INFO geographic information system software S.A. Hoffman.....	21
Development of a platform-independent Paperless Time and Attendance system Greg Huttman	22
The development of tools for construction of interactive information systems L.E. Johnson	23
Automating regression and performance testing of National Water Information System-II software L.W. Lenfest, J.C. Briggs, and C.F. Merk.....	24
Comprehensive approach to production of map illustrations by computer T.D. Liebermann, J.C. Stone, and L.A. Peltz	25
A user's map of the data in the U.S. Geological Survey National Water Information System L.E. Lopp, J.R. Kirk, and I.E. Arroyo	26
Use of remotely sensed data to characterize vegetation in the Red River of the North Basin, Minnesota, North Dakota, and South Dakota D.L. Lorenz	27
Activities of the U.S. Geological Survey Hydrologic Analysis Support Section A.M. Lumb	28
Use of conditional text and hypertext in the user's manual for the U.S. Geological Survey National Water Information System-II S.B. Mathey and J.C. Briggs	29
A microcomputer-based personnel system demonstration using TouchScreen Technology W.R. Matthews	30
An information-request management and accounting system K.W. McFadden	31
Microlink/FFS (Federal Financial System) for UNIX and U.S. Geological Survey Administrative Information System Philip McKinney	32
Implementation of a UNIX-based inventory application at the Rocky Mountain Mapping Center Philip McKinney	33
Administrative business process re-engineering Philip McKinney	34
Scientific visualization at Flagstaff Image Processing Facility, U.S. Geological Survey: Past, Present, and Future Dennis McMacken and Lynda Bellisime	35
A centralized configuration management board in the U.S. Geological Survey C.F. Merk and K.M. Flynn	36
Slide making in a multiplatform environment S.H. Mirzad and W.R. Danskin.....	37
GEONET II Internet routing P.W. Murphy	38
Digital mapping of the national rivers inventory P.H. Murtaugh	39
Use of wide-area information server software to support the National Geospatial Data Clearinghouse D.D. Nebert	40
The use of compact disc-read only memory (CD-ROM) for the storage of data and related programs for UNIX computer operating systems Mark Negri	41
Implementation of the U.S. Department of the Interior electronic acquisition system (IDEAS) D.A. Palmquist	42
Automounting daemon program K.C. Price and Scott Townsend.....	43

An application for the graphical editing and analysis of hydrologic data P.M. Rael and S.M. Trapanese	44
Guidelines for creating user documentation for software in the U.S. Geological Survey R.S. Regan	45
Computer networking of U.S. Geological Survey field offices in the DIS-II environment as an alternative to leased communication lines D.W. Rogers, and M.J. Sweat	46
Data-base logging and journaling systems M.J. Schlesinger	47
Ingres performance issues involving the logging and locking systems G.L. Shank	48
Incorporating electronic maps into U.S. Geological Survey reports S.F. Siwiec and K.L. Southers	49
Statistical and geographic information system analysis of Earth-science information for decisionmaking D.R. Soller and R.L. Bernknopf	50
Computer-science guest-lecture series at Langston University sponsored by the U.S. Geological Survey K.S. Steele	51
Development of digital hydrogeologic map symbols for the U.S. Geological Survey B.E. Taggart and L.E. Menoyo	52
Reference lists for the U.S. Geological Survey National Water Information System-II R.E. Thornberg and B.P. Sargent	53
Laboratory analytical data system S.L. Turner, O.J. Feist, J.A. Lewis, and R.A. Husband	54
Parallelization of a coastal circulation and transport computer model Pearl Wang and H.L. Jenter	55
Applications of geographic information systems and statistics software to a large data base for producing publication-quality figures K.L. Warner, T.L. Arnold, and John Nazimek	56
Real-time monitoring of a hydrologic sensor network C.B. Wierda	57
U.S. Department of the Interior hazardous-waste sites geographic information system N.E. Wingard	58
A collaborative approach to electronic report production T.A. Winterstein and R.A. Miller	59
Author index	61

National Computer Technology Meeting 1994

Scientific Visualization Workshop

Clarion Hotel, New Orleans, Louisiana

April 10-15, 1994

Sunday, April 10, 1994

4:00 pm - 8:00 pm Registration - Grand Ballroom Foyer
6:00 pm - 8:00 pm Welcome Hospitality - Mimosa & Azalea Rooms

Monday, April 11, 1994

7:00 am - 5:30 pm Registration - Grand Ballroom Foyer

COMBINED NCTM/SVW OPENING SESSION - Grand Ballroom Salon B

8:30 am - 8:40 am Introduction of the National Computer Technology Meeting (NCTM)
Gloria Stiltner, Water Resources Division, Reston, Va.
8:40 am - 8:50 am Introduction of Scientific Visualization Workshop (SVW)
Richard MacDonald, Information Systems Division, Reston, Va.
8:50 am - 9:30 am Welcome by Water Resources Division/Information Systems Division
Edward H. Martin, District Chief, Louisiana District
Philip Cohen, Chief Hydrologist, Water Resources Division
James E. Biesecker, Assistant Director for Information Systems
9:30 am - 9:40 am Introduction of Invited Speaker - Gary Cobb, Water Resources Division, Reston, Va.
9:40 am - 10:00 am Invited Speaker
10:00 am - 10:30 am BREAK

NCTM Keynote Session - Grand Ballroom Salon B

10:30 am - 10:40 am Introduction of Keynote Speaker - Colleen Babcock, Water Resources Division,
Tucson, Ariz.
10:40 am - 11:30 am Keynote Speaker - J. Thomas West, Data General Corporation

SVW - Grand Ballroom Salon A

10:30 am - 11:30 am Paper Presentations for SVW
11:30 am - 1:00 pm LUNCH

NCTM TRAINING

1:00 pm - 3:00 pm Training
3:00 pm - 3:30 pm BREAK
3:30 pm - 5:30 pm Training

SVW - Grand Ballroom Salon A

1:00 pm - 5:30 pm Paper Presentations

VENDOR EXHIBITS (NCTM/SVW) - Grand Ballroom Salon C

1:00 pm - 5:30 pm Vendor Exhibits Open
5:30 pm - 7:30 pm Hospitality Kickoff for Vendor Exhibits - Grand Ballroom Foyer

BIRDS OF A FEATHER - Magnolia Room

8:00 pm - 10:00 pm Data General Software Experts discuss technical issues

Tuesday, April 12, 1994

7:30 am - 5:30 pm Registration - Grand Ballroom Foyer

SOFTWARE TOOLS - Audubon E - Moderator, Edward H. Martin, USGS, WRD, Baton Rouge, La.

8:00 am - 8:10 am Announcements

8:10 am - 8:30 am Developing Graphical Applications Using a Very-High-Level Language
BOUCK, Eric, USGS, WRD, Reston, Va.

8:30 am - 8:50 am Parallel Virtual Machine: Capturing the Cycles
BURGESS, Lisa M., and Johnson, Margaret, USGS, ISD, Reston, Va.;
and Pearl Wang, George Mason University, Fairfax, Va.

8:50 am - 9:10 am A Vendor-Independent Fourth-Generation Language for Data Manipulation
and Analysis
FULTON, James L., USGS, WRD, Reston, Va.

9:10 am - 9:30 am The Development of Tools for Construction of Interactive Information Systems
JOHNSON, Larry E., USGS, ISD, Denver, Colo.

MODELING APPLICATIONS - Grand Ballroom B

Moderator, Bill Miller, USGS, GD, Reston, Va.

8:00 am - 8:10 am Announcements

8:10 am - 8:30 am Computer-Based, Three-Dimensional Visualization of Observed Solute
Distributions during the Cape Cod Tracer Test, Massachusetts
HESS, Kathryn M., Kruger, Mary H., Stock-Alvarez, E. Jessica, and
LeBlanc, Dennis R., USGS, WRD, Marlborough, Mass.

8:30 am - 8:50 am Automatic Editing and Graphical Postprocessing of Output from the MODular
Finite Element (MODFE) Model
CZARNECKI, John B., USGS, WRD, Denver, Colo.

8:50 am - 9:10 am The Effect of Data Generalization on the Prediction of Hydrologic Response
HALLAM, Cheryl A., USGS, NMD, Reston, Va.

9:10 am - 9:30 am Parallelization of a Coastal Circulation and Transport Computer Model
WANG, Pearl, George Mason University, Fairfax, Va.; and Jenter, Harry L.
USGS, WRD, Reston, Va.

PANEL DISCUSSION - Audubon D - Moderator, Terry A. Reinitz, USGS, WRD, Reston, Va.

8:00 am - 9:30 am Overview of the Paperless Report Project of the U.S. Geological Survey
HATHAWAY, R.M., USGS, WRD, Tallahassee, Fla.; and Reinitz, T.A., USGS,
WRD, Reston, Va.

Panel members: Andrews, William J., Irwin, George A., Embry, Teresa L.,
Mixson, Patsy R., Tomberlin, James A., Tallahassee, Fla.; Puente, Celso, Reston, Va.

9:30 am - 10:00 am BREAK

SYSTEM ADMINISTRATION APPROACHES - Grand Ballroom Salon B

Moderator, Janice Ward, USGS, WRD, W. Trenton, N.J.

10:00 am - 10:20 am Interoperability of Computer Systems with Dissimilar Architecture: A Case Study
GRIFFIN, Jess W., USGS, WRD, Oklahoma City, Okla.

10:20 am - 10:40 am Administering Internet Network News (INN), the Netnews Server
BOLDT, D.R., USGS, WRD, Reston, Va.

10:40 am - 11:00 am Automounting Daemon Program
PRICE, Ken C., USGS, WRD, NWQL, Arvada, Colo.; and Townsend, Scott,
USGS, WRD, Denver, Colo.

11:00 am - 11:20 am Computer Networking of U.S. Geological Survey Field Offices in the DIS-II
Environment as an Alternative to Leased Communication Lines
ROGERS, David W., and Sweat, Michael J., USGS, WRD, Lansing, Mich.

11:20 am - 11:40 am Slide Making in a Multiplatform Environment
MIRZAD, S.H., and Danskin, W.R., USGS, WRD, San Diego, Calif.

DATA MANAGEMENT APPLICATIONS - Audubon E

Moderator, Jo Ann Macy, USGS, WRD, Indianapolis, Ind.

10:00 am - 10:20 am The U.S. Geological Survey Data Base for U.S. Department of Defense
Environmental Contamination Projects
GERLITZ, Carol N., and Morrell, Eva M., USGS, WRD, NWQL, Arvada, Colo.

10:20 am - 10:40 am Implementation of a UNIX-based Inventory Application at the Rocky Mountain
Mapping Center
McKINNEY, Philip, USGS, AD-OSM, Reston, Va.

10:40 am - 11:00 am Software Development for Remote Entry of Water-Use Data
BRYANT, M. Roland, and Holland, Terrance W., USGS, WRD, Little
Rock, Ark.

11:00 am - 11:20 am An Information-Request Management and Accounting System
McFADDEN, Keith W., USGS, WRD, Atlanta, Ga.

11:20 am - 11:40 am Real-Time Monitoring of a Hydrologic Sensor Network
WIERDA, Clark B., USGS, WRD, Little Rock, Ark.

SVW - Grand Ballroom Salon A

8:00 am - 5:30 pm Paper Presentations

VENDOR EXHIBITS - Grand Ballroom Salon C

8:00 am - 5:30 pm Exhibits Open

11:40 am - 1:00 pm LUNCH

NCTM TRAINING

1:00 pm - 5:30 pm Ingres for System Administrators Panel Discussion -- Audubon D
Moderator, Colleen Babcock, USGS, WRD, Tucson, Ariz.
Data-Base Logging and Journaling Systems, SCHLESINGER, Mark J., USGS,
WRD, Tucson, Ariz.
Ingres Performance Issues Involving the Logging and Locking Systems,
SHANK, Gregory L., USGS, WRD, Lemoyne, Pa.
Managing Relational Data Bases Using Ingres, Beeler, David A., and
O'CONNOR, Michael J., USGS, WRD, Little Rock, Ark.
Tools for Managing the Administrative Information Systems (AIS), MORRIS,
James, USGS, WRD, Lawrence, Kans.
The What, Where, When, and Why's of Checking an Ingres System,
BOSTWICK, Candice M., USGS, WRD, Reston, Va.

1:00 pm - 3:00 pm Training

3:00 pm - 3:30 pm BREAK

3:30 pm - 5:30 pm Training

EVENING ACTIVITIES

5:30 pm - 7:30 pm Hospitality Gathering, NCTM T-Shirt Night - Mimosa & Azalea Rooms

8:00 pm - 10:00 pm Southeast Region Computer Specialists Meeting - Audubon D

8:00 pm - 10:00 pm Northeast Region Computer Specialists Meeting - Audubon E

BIRDS OF A FEATHER - Magnolia Room

8:00 pm - 10:00 pm FrameMaker Techniques - Moderator, Terry A. Reinitz, USGS, WRD, Reston, Va.

Wednesday, April 13, 1994

7:30 am - 5:30 pm Registration - Grand Ballroom Foyer

NATIONAL WATER INFORMATION SYSTEMS - Grand Ballroom Salon B

Moderator, Kathy D. Peter, USGS, WRD, Oklahoma City, Okla.

- 8:00 am - 8:10 am Announcements
- 8:10 am - 8:30 am The Current Status of the National Water Information Systems - II
YORKE, Thomas H., USGS, WRD, Reston, Va.
- 8:30 am - 8:50 am Automating Regression and Performance Testing of National Water Information System-II Software
LENFEST, Leslie W., Briggs, John C., and Merk, Charles F., USGS, WRD, Reston, Va.
- 8:50 am - 9:10 am A User's Map of the Data in the U.S. Geological Survey National Water Information System
LOPP, Lari E., Kirk, James R., and Arroyo, Ileana E., USGS, WRD, Reston, Va.
- 9:10 am - 9:30 am Use of Conditional Text and Hypertext in the User's Manual for the U.S. Geological Survey National Water Information System-II
MATHEY, Sharon B., and Briggs, John C., USGS, WRD, Reston, Va.
- 9:30 am - 10:00 am BREAK
- 10:00 am - 10:20 am Reference Lists for the U.S. Geological Survey National Water Information System-II
THORNBERG, Ruth E., and Sargent, B. Pierre, USGS, WRD, Reston, Va.
- 10:20 am - 10:40 am Laboratory Analytical Data System
TURNER, Sandra L., Feist, Oliver J., Lewis, James A., and Husband, Richard A., USGS, WRD, NWQL, Arvada, Colo.
- 10:40 am - 11:10 am Design and Use of the Data Report Subsystem of the U.S. Geological Survey National Water Information System-II
CAULLER, Stephen J., USGS, WRD, Reston, Va., Beeler, David A., USGS, WRD, Little Rock, Ark.; Baxter, Carmen R., and McKallip, Thomas E., USGS, WRD, Reston, Va.
- 11:10 am - 11:40 am An Application for the Graphical Editing and Analysis of Hydrologic Data
RAEL, Patrick M., USGS, WRD, Little Rock, Ark.; and Trapanese, Susan M., USGS, WRD, Reston, Va.

ADMINISTRATIVE APPLICATIONS IN THE U.S. GEOLOGICAL SURVEY - Audubon E

Moderator, Philip McKinney, USGS, AD-OSM, Reston, Va.

- 8:00 am - 8:10 am Announcements
- 8:10 am - 8:30 am Implementation of the Administrative Information System, First Release, in the Water Resources Division, U.S. Geological Survey—Results and Recommendations
BRADY, Steven J., USGS, WRD, Lawrence, Kans.; Clark, Patricia G., USGS, WRD, Austin, Tex.; Kratz, W. James, USGS, WRD, Carson City, Nev.; and Sabatini, Alice A., USGS, WRD, Reston, Va.
- 8:30 am - 8:50 am Development of a Platform-Independent Paperless Time and Attendance System
HUTTMAN, Greg, USGS, AD-OSM, Reston, Va.
- 8:50 am - 9:10 am Microlink/FFS (Federal Financial System) for UNIX and U.S. Geological Survey Administrative Information System
McKINNEY, Philip, USGS, AD-OSM, Reston, Va.
- 9:10 am - 9:30 am Implementation of the U.S. Department of the Interior Electronic Acquisition System (IDEAS)
PALMQUIST, Donald A., USGS, AD-OPC, Reston, Va.
- 9:30 am - 10:00 am BREAK

MAPPING TECHNIQUES - Audubon E - Moderator, Joel Morrison, USGS, NMD, Reston, Va.

- 10:00 am - 10:20 am Generation of Digital Base Maps for Preparation of Thematic Maps
FREITAG, Sidney J., USGS, WRD, Madison, Wis.
- 10:20 am - 10:40 am Digital Mapping of the National Rivers Inventory
MURTAUGH, Peter H., USGS, NMD, Reston, Va.
- 10:40 am - 11:00 am Development of a 14-Digit Hydrologic Coding Scheme and Boundary Data Set for New Jersey
ELLIS, William H., Jr., and Price, Curtis V., USGS, WRD, W. Trenton, N.J.
- 11:00 am - 11:20 am Applications of Geographic Information Systems and Statistics Software to a Large Data Base for Producing Publication-Quality Figures
WARNER, Kelly L., Arnold, Terri L., and Nazimek, John, USGS, WRD, Urbana, Ill.
- 11:20 am - 11:40 am Incorporating Electronic Maps into U.S. Geological Survey Reports
SIWIEC, Steven F., and Southers, Kim L., USGS, WRD, Lemoyne, Pa.
- 11:40 am - 1:00 pm LUNCH

VENDOR EXHIBITS - Grand Ballroom Salon C

- 8:00 am - 1:00 pm Exhibits Open

NCTM TRAINING

- 1:00 pm - 3:00 pm Training
- 3:00 pm - 3:30 pm BREAK
- 3:30 pm - 5:30 pm Training

EVENING ACTIVITIES

- 5:30 pm - 7:30 pm Hospitality Gathering Mimosa & Azalea Rooms

Birds of a Feather - Magnolia Room

- 8:00 pm - 10:00 pm Toward a Multi-Agency Network for Collection, Transfer, and Display of Real-Time Data, Moderator, Timothy D. Lieberman, USGS, WRD, Carson City, Nev.

Thursday, April 14, 1994

- 7:30 am - 5:30 pm Registration and Information - Grand Ballroom Foyer

COMPUTER ACTIVITIES IN THE U.S. GEOLOGICAL SURVEY - Grand Ballroom Salon B

Moderator, Wendy Budd, USGS, ISD, Reston, Va.

- 8:00 am - 8:10 am Announcements
- 8:10 am - 8:30 am Activities of the U.S. Geological Survey Hydrologic Analysis Support Section
LUMB, Alan M., USGS, WRD, Reston, Va.
- 8:30 am - 8:50 am Administrative Business Process Re-engineering
McKINNEY, Philip, USGS, AD-OSM, Reston, Va.
- 8:50 am - 9:10 am Overview of the Global Change Program
KIRTLAND, David, USGS, NMD, Reston, Va.
- 9:10 am - 9:30 am Scientific Visualization at Flagstaff Image Processing Facility, U.S. Geological Survey: Past, Present, and Future
McMACKEN, Dennis, and Bellisime, Lynda, USGS, ISD, Flagstaff, Ariz.
- 9:30 am - 10:00 am BREAK
Moderator, Richard MacDonald, USGS, ISD, Reston, Va.
- 10:00 am - 10:20 am A Collaborative Approach to Electronic Report Processing
WINTERSTEIN, T.A., and Miller, R.A., USGS, WRD, Mounds View, Minn.
- 10:20 am - 10:40 am NMD Research Lab Overview
MORRISON, Joel, USGS, NMD, Reston, Va.

- 10:40 am - 11:00 am The Use of Compact Disc-Read Only Memory (CD-ROM) for the Storage of Data and Related Programs for UNIX Computer Operating Systems
NEGRI, Mark, USGS, WRD, Reston, Va.
- 11:00 am - 11:20 am Telecommunications Infrastructure of the U.S. Geological Survey
BONUGLI, Richard J., USGS, ISD, Reston, Va.
- 11:20 am - 11:40 am GEONET II Internet Routing
MURPHY, Patrick W., USGS, ISD, Menlo Park, Calif.

GUIDELINES AND STANDARDS - Audubon D -

Moderator, J. Nicholas Van Driel, USGS, NMD, Reston, Va.

- 8:00 am - 8:10 am Announcements
- 8:10 am - 8:30 am Comprehensive Approach to Production of Map Illustrations by Computer
LIEBERMANN, Timothy D., Stone, J. Christopher, and Peltz, Lorri A., USGS, WRD, Carson City, Nev.
- 8:30 am - 8:50 am Guidelines for Creating Software User Documentation in the U.S. Geological Survey
REGAN, R.S., USGS, WRD, Reston, Va.
- 8:50 am - 9:10 am A Centralized Configuration Management Board in the U.S. Geological Survey
MERK, Charles F., and Flynn, Kathleen M., USGS, WRD, Reston, Va.
- 9:10 am - 9:30 am Development of Digital Hydrogeologic Map Symbols for the U.S. Geological Survey
TAGGART, Bruce E., and Menoyo, Luis E., USGS, WRD, San Juan, P.R.
- 9:30 am - 10:00 am BREAK

GEOGRAPHIC INFORMATION SYSTEM APPLICATIONS - Audubon D

Moderator, Douglas Posson, USGS, ISD, Denver, Colo.

- 10:00 am - 10:20 am Using a Geographic Information System to Derive Urban Land Use from Population Data
HITT, Kerie J., USGS, WRD, Reston, Va.
- 10:20 am - 10:40 am Statistical and Geographic Information System Analysis of Earth-Science Information for Decisionmaking
SOLLER, David R., and Bernknopf, Richard L., USGS, GD, Reston, Va.
- 10:40 am - 11:00 am A Site Verification Program Using ARC/INFO Geographic Information System Software
HOFFMAN, Scott A., USGS, WRD, Lemoyne, Pa.
- 11:00 am - 11:20 am Use of Remotely Sensed Data to Characterize Vegetation in the Red River of the North Basin, Minnesota, North Dakota, and South Dakota
LORENZ, David L., USGS, WRD, Mounds View, Minn.
- 11:20 am - 11:40 am U.S. Department of the Interior Hazardous-Waste Sites Geographic Information System
WINGARD, Norman E., USGS, WRD, Reston, Va.
- 11:40 am - 1:00 pm LUNCH

SPECIAL MEETINGS

- 1:00 pm - 3:30 pm Information Systems Council Meeting - Magnolia Room
- 1:00 pm - 3:00 pm DIS Technical Support Meeting - Cypress Room

NCTM TRAINING

- 1:00 pm - 4:30 pm Panel Discussion Internet Usage - Audubon D
Moderator Doug D. Nebert, USGS, WRD, Reston, Va.
- Use of Wide-Area Information Server Software to Support the National Geospatial Data Clearinghouse, NEBERT, Douglas D., USGS, WRD, Reston, Va.
- The Hydrologic Models Summary (HYMS): Making Software Information Accessible through the Wide Area Information Servers (WAIS) Software, GOZÉ, Michèle Y., USGS, WRD, Reston, Va.
- Selected Water Resources Abstracts in WAIS, KNAPP, George, USGS, WRD, Reston, Va.

Mosaic as an Internet Browsing Tool, TOWNSEND, Scott, USGS, WRD, Denver, Colo.
USGS-Wide Information Clearinghouse, MILLER, Bill, USGS, GD, Reston, Va.

1:00 pm - 3:00 pm Training
3:00 pm - 3:30 pm BREAK
3:30 pm - 5:30 pm Training

EVENING ACTIVITIES

8:00 pm - 1:00 am The NCTM Lagniappe Party - Audubon DE

Friday, April 15, 1994

FUTURES SESSION - Grand Ballroom Salon B -

Moderator, David E. Click, USGS, WRD, Lemoyne, Pa.

8:30 am - 8:50 am Regional GIS Labs, Van Driel, James Nicholas, USGS, NMD, Reston, Va.
8:50 am - 9:00 am Introduction of Guest Speaker - Thomas C. Wood, USGS, WRD, Reston, Va.
9:00 am - 9:30 am Guest Speaker, James Fulton, NCD, "The Future of X"
9:30 am - 10:00 am BREAK
10:00 am - 10:45 am A Report on Technology Trends and Developments 1994-2000
Richard Hollway, USGS, WRD, Portland, Oreg.; and Douglas Posson, USGS, ISD,
Denver, Colo.
10:45 am - 11:30 am The Status of DIS-II+
Gloria Stiltner, USGS, WRD, Reston, Va.; and Richard Hollway, USGS, WRD,
Portland, Oreg.
11:30 am - 12:00 m Close of Meeting - James Daniel

Demonstrations

Computer-Science Guest-Lecture Series at Langston University Sponsored by
the U.S. Geological Survey, STEELE, Karen S., USGS, WRD, Oklahoma City, Okla.
(located in the Registration area)

A Microcomputer-based Personnel System Demonstration Using TouchScreen
Technology, MATTHEWS, R. William, USGS, ISD, Reston, VA (located in the Vendor
exhibit area)

Demonstration of a Digital Compact Disc Containing Navajo and Hopi Indian
Reservation Data for Use in Schools to Teach Remote Sensing, ACOSTA, Alex V.,
USGS, ISD, Flagstaff, Ariz. (located in the Vendor exhibit area)

The DIS Program Office sponsored "Nerds R Us" demonstrations on software tools and
techniques (located in the Vendor exhibit area)

Abbreviations

AD-OPC Administrative Division-Office of Procurement and Contracts
AD-OSM Administrative Division-Office of Systems Management
GD Geologic Division
ISD Information Systems Division
NCTM National Computer Technology Meeting
NMD National Mapping Division
NWQL National Water Quality Laboratory
SVW Scientific Visualization Workshop
USGS U.S. Geological Survey
WRD Water Resources Division

DEMONSTRATION OF A DIGITAL COMPACT DISC CONTAINING NAVAJO AND HOPI INDIAN RESERVATION DATA FOR USE IN SCHOOLS TO TEACH REMOTE SENSING

ACOSTA, Alex V., USGS, ISD, 2255 N. Gemini Drive, Flagstaff, Arizona 86001

A digital compact disc with read-only memory (CD-ROM) containing remotely sensed data, introductory material on image processing, and multimedia presentations was developed in a multiagency/division effort between the Information System Division, Bureau of Indian Affairs, Geologic Division's Office of Scientific Publications, and Northern Arizona University. The development of this information on CD-ROM was part of an outreach activity aimed at the pre-college educational community.

Traditional methods used to teach science and mathematics to Indian Reservation students can be augmented through the use of a visual and nontraditional environment of remotely sensed data that can be inexpensively distributed through CD-ROM media. Data from Landsat sensors or other imaging systems can be used in a visual environment to expose students to the concept of the electromagnetic spectrum. Different algorithms for contrast enhancement or digital filtering can be applied to the data to demonstrate the effects of mathematical processes. The images and visual representations presented can provide the impetus to interest and challenge students in the fields of science and mathematics. The introductory material provided is used to make the transition from the visual to the traditional methods of teaching.

Multimedia presentations pertaining to culture, and history are included to perpetuate traditions and instill pride to manage Reservation resources for the benefit of present and future generations.

MANAGING RELATIONAL DATA BASES USING INGRES

BEELER, David A., and *O'CONNOR*, Michael J., 700 West Capitol Avenue, Little Rock, AR 72201

Many of the traditional data bases that are maintained by the U.S. Geological Survey are being redesigned to use relational data base technology available as a result of the implementation of the Distributed Information System-II. The Arkansas District has been involved in the development of software for the National Water Information System-II (NWIS-II) and has maintained as many as three relational Ingres data bases for software development. The District also has installed and maintains the Administrative Information System, a separate relational Ingres data base, in conjunction with the NWIS-II software development data bases.

A variety of tools is required to efficiently maintain the integrity and security of multiple data bases in a District computing environment. These tools include utility programs to provide data checkpoints, backups, and verification, as well as utility programs for reviewing data in tables, granting permissions, and routine cleanup of data base tables. The Arkansas District experience in maintaining multiple relational data bases may be useful to other District that are beginning to deal with these issues.

ADMINISTERING INTERNET NETWORK NEWS (INN), THE NETNEWS SERVER

BOLDT, D.R., USGS, WRD, 12201 Sunrise Valley Drive, Reston, VA 22092

Internet Network News (INN) has replaced the Continuum, an electronic bulletin board used by the Water Resources Division, on its Prime minicomputers. Having a local netnews-server can boost responsiveness, and allows the creation of local newsgroups, but presents a host of management issues. This talk provides an overview of how the news-server software works, and how it can be customized for local use. Management of an INN news-server includes obtaining news articles from other news-servers, providing news articles to other sites, expiring (deleting) and archiving old articles, monitoring disk space and inode usage, and maintaining data bases providing information on newsgroups, distribution codes, and connection permissions.

TELECOMMUNICATIONS INFRASTRUCTURE OF THE U.S. GEOLOGICAL SURVEY

BONUGLI, Richard J., USGS, ISD, 12201 Sunrise Valley Drive, Reston, VA 22092

An information services division within the U.S. Geological Survey (USGS) provides the telecommunications infrastructure and support necessary to meet the scientific mission of the bureau and its associated administrative support facilities. In addition, the USGS provides telecommunications services to support the varied missions of several other Federal government agencies. This telecommunications infrastructure, called GEONET, is based on a transmission technology known as cell-relay technology and on a transmission protocol known as the Asynchronous Transfer Mode (ATM).

GEONET is a proprietary-based ATM network made up of cell (ATM) switches. Recently, GEONET expanded from 3 to 11 cell switches located throughout the country at major USGS sites. These cell switches are connected by high-speed telecommunications lines known as T1 that transmit information at a rate of 1.5 million bits per second (Mbps). The cell switches are capable of multiplexing data, voice, and video information in small fixed-sized 24-byte cells. While the international ATM standards stipulate 53-byte cells at T3 (44.736 Mbps) and higher rates, the cell switches employed use 24-byte cells for higher efficiency and performance at T1 rates. This technology provides the USGS with an efficient, high-performance, multimedia national telecommunications network.

At each cell switch, a multiprotocol router collects and routes data from one or more Local Area Networks (LAN's). Data from these LAN's destined for a site on the wide-area network passes to the cell switch through the frame-relay packet mode service, and is then switched to another cell switch on GEONET.

All 11 major USGS sites have the need for data transmission. In addition, some sites can also appropriately support voice and video transmission. Voice is interfaced to the cell switch from digital voice switches, and video is interfaced to the cell switch from video equipment.

The ATM benefits of bandwidth on demand, bandwidth pooling, multimedia format, and scalability provide the USGS and other Federal agencies using GEONET with high-performance LAN-to-LAN and LAN-to-wide area traffic, interactive graphics, and videoconferencing. In the future, ATM benefits are expected to provide video email, distance learning, hypermedia documents, and desktop videoconferencing.

The USGS has a contract with a vendor to provide the hardware and software for the cell switches and multiprotocol routers necessary for GEONET. In addition, the USGS is provided an integrated network management system. The system consists of a combination of hardware and software for managing cell switches and multiprotocol routers. In the near future, the USGS will also be provided an overall network management system to integrate the management of all telecommunications elements. The USGS maintains a duplicate, read-only version of this network management setup to assist in trouble-shooting telecommunications problems.

Future plans call for the ATM-based network to be fully compliant with the ATM international standards. USGS plans to deploy the ATM technology to operate on LAN's. GEONET has the potential to become the telecommunications infrastructure for the entire U.S. Department of the Interior.

DEVELOPING GRAPHICAL APPLICATIONS USING A VERY-HIGH-LEVEL LANGUAGE

BOUCK, Eric, USGS, WRD, 12201 Sunrise Valley Drive, Reston, VA 22092

Scientific applications benefit from graphical user interfaces. The time required to create graphical user interfaces with low level development tools can be exorbitant. High level tools to speed development are available, but these tools require costly licensing arrangements with vendors and do not guarantee portability to future platforms.

The freely available Tool Command Language (Tcl) is a very-high-level interpreted language designed to be used as a common command language for many different applications. Tcl has a very simple syntax and command structure that serves to reduce development time at the expense of some computational performance and error detection. Tcl can be embedded and extended through the use of its C language library, allowing for the implementation of certain routines through C function calls. Tk is a Tcl extension that facilitates the construction of graphical user interfaces. A feature of Tk is the ability to send commands between Tk based applications. The strength of the combination of Tcl and Tk lies both in the ability to create graphical applications rapidly and in the connectivity that results from multiple applications sharing the same command language. Through new and existing extensions, Tcl/Tk can provide a powerful development environment.

IMPLEMENTATION OF THE ADMINISTRATIVE INFORMATION SYSTEM, FIRST RELEASE, IN THE WATER RESOURCES DIVISION, U.S. GEOLOGICAL SURVEY—RESULTS AND RECOMMENDATIONS

BRADY, Steven J., USGS, WRD, 4821 Quail Crest Place, Lawrence, KS 66049; **CLARK**, Patricia G., 8011 Cameron Road, Building 1, Austin, TX 78754-3898; **KRATZ**, W. James, 333 West Nye Lane, Room 203, Carson City, NV 89706; and **SABATINI**, Alice A., USGS, WRD, 12201 Sunrise Valley Drive, Reston, VA 22092

The Administrative Information System (AIS), designed and developed by the U.S. Geological Survey (USGS), was released as scheduled in January 1993, and 88 sites throughout the country began immediate installation, data transfer, and use. The AIS includes many new features not present in previous systems: simultaneous access by many users; graphical user interface in a UNIX-based windowed environment; and a distributed data base that facilitates use and reporting at single and multiple cost center sites, area, region, and division levels. The first release included capabilities to handle funding, expenditure tracking, and selected parts of project management. All cost centers will use the software to close accounts for fiscal year 1993.

In February 1990, the USGS began to design the replacement of existing administrative management systems from the current system housed on PRIME minicomputers to a UNIX-based distributed environment. Twelve user work groups were established to identify functional user requirements and process flow diagrams. Work-group reports were used to develop a system specification design document. A development team was organized in Lawrence, Kansas, to write the program code using the design document. The development of the AIS and its installation is scheduled for release in four parts: Financial Management, Project and Reports Management, Human Resources Management, and Organization Management. Releases will extend through 1995.

A training plan that is effective, timely, cost efficient, and reaches the largest possible number of users was designed for AIS implementation. A 6-member group of instructors with a broad range of experience and expertise provided instruction to a national team of 32 trainers in December 1992 at the U.S. Geological Survey National Training Center in Denver, Colorado. The 32 trainers then were given the responsibility for providing hands-on instruction to other users within their respective geographic areas. A questionnaire, completed by most attendees at the end of the national training session, rated the training as positive in method and content. The replies to a second questionnaire to evaluate the instruction provided by the national trainers were less than positive and indicated that problems were encountered using the AIS and training others in its use.

Three major problems found using AIS were as follows: (1) some sites did not have the equipment necessary to run the software when it was released; (2) Data General hardware, the UNIX environment, and Ingres software were new to USGS personnel and knowledge of those capabilities was limited; and (3) the transfer of data from existing administrative management systems was more complicated than had been anticipated. Other problems included: (1) communication between the development and implementation teams and the users was insufficient; (2) training was held too early during implementation, allowing information to be forgotten before it could be applied; (3) training provided to field users had inconsistent results; and (4) software was inadequately tested prior to release.

Recommendations for software implementation and related training in its use include the following: (1) ensure that installation sites have adequate equipment and that data-base administrators and users have received instruction in basic operational techniques; (2) expand software testing to detect programming and functional problems; (3) improve the communication between programmers and users to share information and problem resolution; (4) adhere to selection criteria for choosing individuals to serve as trainers; and (5) provide training immediately before application to increase retention of the material.

SOFTWARE DEVELOPMENT FOR REMOTE ENTRY OF WATER-USE DATA

BRYANT, M. Roland, and **HOLLAND**, Terrance W., 700 West Capitol Avenue, Little Rock, AR 72201

The Arkansas Soil and Water Conservation Commission (ASWCC) and the U.S. Geological Survey (USGS) are working cooperatively to collect and store water-use data for the State. Approximately 53,000 reporting forms for ground- and surface-water withdrawals for agriculture and irrigation are submitted to ASWCC annually through the Conservation District Offices in 26 eastern Arkansas counties. Also, about 2,000 water-use registration forms are processed annually. Completion of these registration forms usually involves an interview between the water user and Conservation District personnel.

The current process requires a great deal of paper handling by Conservation District office, ASWCC, and USGS personnel. This reporting process includes the grouping of water-use registration forms (one form per well or surface-water diversion) by landowner or diverter, conducting interviews with farmers, computing irrigation and agricultural water use by crop type, determining monthly and annual water-use totals, and collecting a registration fee and filling out a receipt of payment for every well or diversion reported by the water user.

Completed water-use reporting forms are received and logged in by the ASWCC, and forwarded to the USGS for entry of the water-use data into the National Water Information System (NWIS) Site-Specific Water-Use Data System (SSWUDS) during an 8-month period (March-September). The USGS produces preprinted forms for the next reporting period, certificates documenting surface-water diversions, and cards reminding users of the start of a new reporting period. These documents are provided to ASWCC for mailing to registered water users.

To streamline the reporting process and minimize the large amount of paper forms, the USGS is designing a local data base and writing supporting computer software, that will reside and be maintained on the Conservation District Office computer. With this software, the Conservation District Office personnel will be able to enter water-use registration information into the office computer during the interview with the water user. In addition, they will be able to maintain a local county data base that can be used to answer local questions about water use. Other functions of the water-use reporting system include: performing mathematical computations to ensure irrigation and agricultural data are summed correctly, providing a table for crop application rates by crop type for those users that must estimate the amount of water that was withdrawn, computing the number of wells or surface-water diversions for each owner and the amount of money owed for water-use reporting fees, and enabling the Conservation District personnel to print receipts for water-use fees. In order to keep the SSWUDS (and eventually NWIS-II) updated properly, the local Conservation District Office personnel will be able to copy new data to a file that can be written to a diskette, mailed to the ASWCC and forwarded to the USGS, and loaded into the NWIS data base. This will eliminate the handling of thousands of paper forms.

PARALLEL VIRTUAL MACHINE: CAPTURING THE CYCLES

BURGESS, Lisa M., and **JOHNSON**, Margaret, USGS, ISD, 804 National Center, Reston, VA 22092; **WANG**, Pearl, George Mason University, Computer Sciences Department, Fairfax, VA 22030

As scientists begin to push the limits of single-processor desktop computers, the advantages of parallel processing are becoming critical. The use of parallel processing techniques to increase numeric computation capability, however, comes with unexpected costs of time and money: converting programs, acquiring software oriented to programming in the parallel processing environment, attending training courses, and possibly buying new hardware. Although scientists could readily make use of more Central Processing Unit (CPU) power, they are frequently unable to obtain the funding for the software conversion of programs to take advantage of this CPU power. Becoming productive in the parallel processing environment is often not advantageous to the scientists due to the costs of time and money.

Parallel Virtual Machine (PVM) may be the answer to the problem of these costs. As a public domain programming environment, PVM can take advantage of unused CPU cycles available on a network of UNIX-based computers. In the PVM environment, several computers can be connected into a virtual machine thus creating a "parallel virtual machine." One advantage that PVM has to offer is that it allows a heterogeneous collection of computers to cooperate in completing a task. Because the U.S. Geological Survey (USGS) maintains a computing environment that is heterogeneous in nature, this is an important feature. The time needed to learn to program in the PVM environment is reduced by the fact that PVM programs are written in either FORTRAN or C with embedded PVM routines to handle such tasks as message passing and synchronization. Thus, an entirely new language does not need to be learned.

The USGS has installed PVM on several computers and has begun experimenting with the capabilities of parallel processing. Currently, two prototypes are under development: one using a geochemical model for aqueous solutions and the other using an image processing application. These exiting applications are being ported into the PVM environment and studies will be done to quantify the processing of these data sets and compare results to traditional computing methods. Numeric studies will be performed based on the test results obtained from sample computations to determine if the increase in performance, if any at all, outweighs the hours used in converting these applications. These and future prototypes will serve as a basis for evaluating the effectiveness of PVM in Earth science computing environments.

DESIGN AND USE OF THE DATA REPORT SUBSYSTEM OF THE U.S. GEOLOGICAL SURVEY NATIONAL WATER INFORMATION SYSTEM-II

CAULLER, Stephen J., USGS, WRD, 12201 Sunrise Valley Drive, Reston, VA 22092; **BEELE**R, David A., USGS, WRD, 700 West Capitol Avenue, Little Rock, AR 72201; **BAXTER**, Carmen R., and **McKALLIP**, Thomas E., 12201 Sunrise Valley Drive, Reston, VA 22092

The National Water Information System-II (NWIS-II) is being developed by the U.S. Geological Survey (USGS) to replace several disparate water data-base systems with a single multidiscipline data-base system. The NWIS-II application software is written in a fourth-generation language, Ingres Windows4GL, which provides a graphical interface to the NWIS-II Ingres relational data base. Application software that interacts with the NWIS-II data base consists of several integrated subsystems, each with distinct functionality and purpose. The Data Report Subsystem (DRS) of the NWIS-II is described in this paper.

The DRS was designed to accommodate USGS users' need to generate flexible, near-publication-ready data reports and general-purpose data summaries. It allows users to select specific report types, each consisting of a distinct layout and format. Report formats are divided into fixed-format postscript, flexible-format postscript, and American Standard Code for Information Interchange (ASCII) text output. The intended use of the report, and whether it is published or not, governs the category in which it is included. Upon selecting a particular report format and specifying a period of record to be included in the report, the user is led through one or more data-selection screens. Each selection screen consists of a theme or logical subdivision of water-data attributes, such as sites (where data are collected), samples (type of environmental sample and date/time of collection), and/or parameter sets (the physical or chemical constituents measured on the sample). The specifications entered in each selection screen are used to define the final data elements selected from the data base to be included in the report. Results from each selection screen can be saved to a file to be reused for future report generation.

Postscript reports are created by retrieving the specified data and writing the data stream, commingled with Maker Interchange Format (MIF) strings, to an MIF file. The MIF file is imported into a blank FrameMaker template, creating a word-processor-formatted document that can be printed on a postscript-compatible printer. ASCII reports are created by retrieving the specified data and generating the report layout using Ingres Report-Writer.

AUTOMATIC EDITING AND GRAPHICAL POSTPROCESSING OF OUTPUT FROM THE MODULAR FINITE ELEMENT (MODFE) MODEL

CZARNECKI, John B., USGS, WRD, Building 53, Box 25046, Denver Federal Center, Denver, CO 80225

Transient simulations of ground-water flow in the vicinity of Yucca Mountain, Nevada (the potential site of a repository for high-level nuclear waste), were made using the U.S. Geological Survey MODular Finite Element (MODFE) Model. These simulations were used to predict possible changes in water-table altitude and ground-water flow as a result of a potential increase in recharge and a change in local transmissivity over a period of 20,000 years. The resulting computer output represented hundreds of time steps, prohibiting hand processing of each time step. Because of the need to graphically examine these simulation results, hydraulic-head values from each reported time step were processed using a variety of automatic editing routines and nested script files on UNIX-based computers.

To extract hydraulic-head values for each time step, a script file, which invokes the vi editor, is used to search for the occurrence of a specific string of text written at the start of each time step in the MODFE output file and to copy the heads for those time steps to separate files. These files use the time step value, in seconds (for example, 0.53003E+07), as part of the file name for easy identification. By modifying saved directory listings of only these files, additional script files are invoked to run programs to calculate the change in hydraulic head from initial head conditions, edit control files for use with a contouring program, run the program, and print contour plots. A similar procedure is available for ground-water flow vector processing and plotting. The use of script files in postprocessing MODFE output greatly increases the efficiency of visualization and analysis of model results.

DEVELOPMENT OF A 14-DIGIT HYDROLOGIC CODING SCHEME AND BOUNDARY DATA SET FOR NEW JERSEY

ELLIS, William H., Jr., and *PRICE*, Curtis V., USGS, WRD, 810 Bear Tavern Road, Suite 206, W. Trenton, NJ 08628

An interagency effort to define and delineate 14-digit hydrologic cataloging units in the State of New Jersey is underway. Agencies involved include the U.S. Geological Survey (USGS); the New Jersey Department of Environmental Protection and Energy (NJDEPE); and the U.S. Department of Agriculture, Soil Conservation Service (SCS). The 14-digit units are needed for use in water-quality-management programs that will include watershed monitoring, study, and regulation. Standards and guidelines for the development of the 14-digit units were established by an interagency committee. The final 14-digit basin data base will be in digital-line-graph format on floppy disk.

An 11-digit coding scheme was devised by the NJDEPE and SCS for water-planning purposes in the early 1980's. This delineation scheme was checked for accuracy and updated where necessary and will be used as the basis of the 14-digit basin delineation. Updates include the addition of 11-digit divides in the intercoastal waterways of New Jersey based on areas of limited tidal mixing.

Most of a polygon data set of drainage basins that were digitized and updated by the USGS in the late 1980's will be incorporated into the 14-digit basin data base. This data set consists of more than 3,000 drainage-basin delineations prepared for flow estimates and drainage-area determinations. This existing 14-digit data set is currently being checked and edited to ensure its accuracy. The availability of these previously developed data sets has greatly facilitated the development of the new 14-digit hydrologic cataloging units.

GENERATION OF DIGITAL BASE MAPS FOR PREPARATION OF THEMATIC MAPS

FREITAG, Cidney J., USGS, WRD, 505 Science Drive, Madison, WI 53711

The Cartographic and Publication Program of the Water Resources Division, Northeastern Region has implemented procedures using a geographic information system (GIS) or a combination of a GIS and a vector-based drawing program to produce publication-quality base maps. Thematic overlays can be added by digital or analog methods. Use of a base map derived from the same data base used for scientific work allows smooth transition from analysis to publication stages of a project.

The base map generation process begins with the acquisition of digital data and ends with prepress film products. Steps in the process include (1) analytical data processing to combine and register layers of data into a continuous dataset useful for scientific work; (2) cartographic processing to add annotation and generalize the data for small map scales; and (3) cartographic refinement to assign symbology and choose base information appropriate for project publications.

Thematic-data overlays may be generated digitally as part of the analytical process and included as part of the data base. Projects not using GIS can still enjoy some of the benefits of digital-map production by importing a GIS-derived base map into a drawing program where thematic data can be incorporated.

A VENDOR-INDEPENDENT FOURTH-GENERATION LANGUAGE FOR DATA MANIPULATION AND ANALYSIS

FULTON, James L., USGS, WRD, 12201 Sunrise Valley Drive, Reston, VA 22092

Fourth-generation languages (4GL's) are very high-level programming languages that include facilities for data management and analysis. Examples of commercial 4GL's that have been widely used within the U.S. Geological Survey include INFO, ARC/INFO, SAS, P-Stat, Ingres SQL, and Ingres Windows 4GL. The use of these languages provides many advantages over the use of low-level programming languages, such as Fortran or C, including reduced training requirements, shorter development times, and fewer lines of code to be maintained. Unfortunately, there are few standards for 4GL's and each vendor's 4GL differs from other vendors' 4GL's in significant ways. Programs written using commercial 4GL's are typically non-portable and commercial 4GL's can not readily work with other vendor's software. A disadvantage of commercial 4GL's is that although less training is required to master a 4GL than is required for a low-level language, retraining and reprogramming are required every time the 4GL vendor changes.

The UNIX operating system provides a vendor-independent 4GL alternative. The UNIX shells, such as the Bourne or Korn shells, in combination with specialized programs provide a very high-level programming environment that is highly portable and flexible, and that provides functionality equalling or exceeding that of commercial 4GL's. A key feature of the UNIX environment and operating philosophy is that many different programs can be integrated through UNIX inter-process communication to perform a variety of tasks. The UNIX shells control the execution of application programs and the flow of data between them. If existing programs don't exist to solve a particular task, it is easy to build one or more small programs that supply the missing functionality and to integrate them with the rest of the environment.

A useful set of programs for data manipulation and analysis is the Relational Database System (RDB). The RDB system is available at no cost and provides a simple, flexible, self-documenting data format and a set of small programs for data-base management, data selection and transformation, data restructuring, quality assurance, and simple statistical analysis. RDB was designed to be flexible and it is easy to move RDB data between different computer hardware systems and software applications, and to develop new RDB programs. The simple format of RDB files provides a basis for application integration because simple translation software is provided for converting between various specialized application formats and the RDB format and the conversion software can be applied directly to the stream of data passing between applications. The various RDB programs in combination with the UNIX shells provide the data management and analysis facilities normally associated with a 4GL.

THE U.S. GEOLOGICAL SURVEY DATA BASE FOR U.S. DEPARTMENT OF DEFENSE ENVIRONMENTAL CONTAMINATION PROJECTS

GERLITZ, Carol N., and *MORRELL*, Eva M., USGS, WRD, National Water Quality Laboratory, 5293 Ward Road, Arvada, CO 80002

Large and variable data sets generated by the U.S. Geological Survey's Department of Defense Environmental Contamination (DODEC) projects will not fit into the current (1993) National Water Information System (NWIS). To provide data-handling capability for these DODEC projects until NWIS-II is available, an interim DODEC relational data base has been developed using Ingres on Data General workstations.

The DODEC data base consists of tables for storing site descriptions, well information, and results of chemical analyses of soil, water, and plant- and animal-tissue samples. Data-base users can enter data into site and well tables by means of a menu-driven interface. Chemical data—received from the laboratory in digital format—can be automatically loaded into the data base using embedded Structured Query Language (SQL) C programs. The chemical data can be related to information about specific sampling locations stored in the site and well tables.

Advantages of the DODEC data base, in addition to providing space for the variable data, include assistance with quality assurance and quality control of data, ease of compiling summary tables for various reports, and direct access from other software (for example, ARC/INFO, SAS, G2, and Statit). In addition, U.S. Air Force DODEC projects can retrieve data tables in the format required by the Air Force Installation Restoration Program Information Management System (IRPIMS).

Successful operation of the DODEC data base depends on careful preparation of equipment and personnel by following a specific list of hardware, software, and training requirements prior to installation. The list of requirements is available to prospective users.

THE HYDROLOGIC MODELS SUMMARY (HYMS): MAKING SOFTWARE INFORMATION ACCESSIBLE THROUGH THE WIDE AREA INFORMATION SERVERS (WAIS) SOFTWARE

GOZÉ, Michèle Y., USGS, WRD, 12201 Sunrise Valley Drive, Reston, VA 22092

Providing software support for the U.S. Geological Survey (USGS) includes making known what software is available and what computing needs can be met by that software. The Wide Area Information Servers (WAIS) software has been employed by the Hydrologic Analysis Support Section of the USGS Office of Program Coordination and Technical Support to provide an easily accessible text data base of software descriptions called the Hydrologic Models Summary (HYMS).

Well-defined categories of information describe each of the programs in HYMS. These categories include: an abstract describing what the program does, the theory behind the computational scheme, the input and output options and/or requirements, references to any published documentation, the computer platforms on which the program is available, descriptions of where and how the program has been successfully or unsuccessfully applied, and contacts for computer and technical support.

HYMS is stored on-line in Reston, Virginia, for immediate query by users of WAIS client software. Use of HYMS at a given site involves a few simple steps that the system administrator can perform to make HYMS directly available to all the users at that site. Once local access to HYMS has been established, obtaining information from the data base is accomplished by entering one or more words that are used to search the text for information on the program of interest.

Creation of the HYMS data base, or any other text data base, involves relatively simple modification to the public domain C source code. Three basic functions are called in a predetermined order to process a text file and index its contents for WAIS query and retrieval. The WAIS software on the workstation that serves the data base can also be modified to fine tune what will be retrieved from the data base for each query.

INTEROPERABILITY OF COMPUTER SYSTEMS WITH DISSIMILAR ARCHITECTURE: A CASE STUDY

GRIFFIN, Jess W., USGS, WRD, 202 N.W. 66 Street, Oklahoma City, OK 73116

The Oklahoma District of the U.S. Geological Survey is conducting a study using a Local Area Network (LAN) and the X Window System (X) to provide a Microsoft Disk Operating System (MS-DOS) server. X, a standard open network graphics windowing system, allows different operating systems to use a consistent user interface. An MS-DOS server is a personal computer (PC) providing MS-DOS services to the LAN.

Quarterdeck's DESQview/X and Sun's PCNFS software were evaluated. DESQview/X uses X to display UNIX-based programs on the PC. It also allows the workstation to run PC-based software and display output. PCNFS makes available UNIX-based file systems to the PC.

Installation and setup of software on the PC was time-consuming. The software provided automatic installation, but configuration files required editing to account for specific hardware devices. Most of the X-window software displayed on the PC performed well; however, DESQview/X could not produce a 1280 x 1024 pixel display. Multiple users accessing a PC file created problems such as corrupting program data and in some instances caused the PC to lock up. Additionally, integration of UNIX file systems required either mounting each workstation's logical disk as a logical drive on the PC, or creating a common user disk space.

Costs and benefits of providing an MS-DOS server must be weighed by each office. System administration of the MS-DOS server is complicated, yet may ease operations if the MS-DOS server can replace multiple PC's.

THE EFFECT OF DATA GENERALIZATION ON THE PREDICTION OF HYDROLOGIC RESPONSE

HALLAM, Cheryl A., USGS, NMD, 12201 Sunrise Valley Drive, Reston, VA 22092

As more land-based process information is included in the predominantly atmospheric general circulation models (GCM), the generalization of descriptions of the Earth's surface contained in digital elevation models (DEM) and other land characterization data sets is becoming more important. Many lower resolution data bases used in global models are being assembled from groups of higher resolution regional data bases.

As the regional effects of global change are studied, and the information generated by continental and global models provides data sources for the regional hydrologic models, the validity of those regional models' predictions may come into question. Although efforts are being made to minimize the amount of information lost in the generalization process, some loss is inevitable. It is important to understand the effect that such an information loss will have on the models in which these data are used.

This research project examined the sensitivity of a widely used precipitation-runoff model to data generalization. A controlled experiment was conducted to determine how runoff predictions were affected by changes in the spatial resolution of elevation-based input parameters.

Preliminary results suggest that, for the 17 years tested, the elevation data resolution had a significant effect on the prediction of monthly runoff totals, but the annual runoff totals were unaffected by generalization of the elevation data from 100 to 1,000 meters. In addition, the changes in predicted monthly runoff showed a seasonal pattern. If such runoff differences hold up under statistical tests, they could suggest serious seasonal prediction errors when input data are generalized.

OVERVIEW OF THE PAPERLESS REPORT PROJECT OF THE U.S. GEOLOGICAL SURVEY

*HATHAWAY, R.M., USGS, WRD, 227 N. Bronough St., Suite 3015, Tallahassee, FL 32301; and
REINITZ, T.A., USGS, WRD, 12201 Sunrise Valley Drive, Reston, VA 22902*

The Paperless Report Project is a cooperative effort of the U.S. Geological Survey (USGS), Office of the Assistant Chief Hydrologist for Scientific Information Management, and the Florida District of the USGS to develop, evaluate, and test procedures for producing publications in a fully electronic environment. A Water-Resources Investigations Report "Effects of Selected Dairy Farms on Ground-Water Quality in North Florida" by William A. Andrews is being prepared from draft to camera-ready stages using Data General workstations and software packages that include FrameMaker, CorelDRAW, USGS-G2, Statit, and Statistical Analysis Software (SAS), and local and wide-area networks. The techniques used at each stage are documented in an electronic journal and recommendations for the production of paperless reports will be published in an Open-File Report.

Training for the various software packages, including CorelDRAW and FrameMaker, has been provided to project participants. FrameMaker training covered both basic and advanced features, such as creating complex equations and tables. Refinements have been made to FrameMaker templates, and USGS-G2 software has been revised to resolve difficulties experienced in importing ASCII data files.

The author completed the draft report in April 1993 and the report has undergone precolleague reviews by the Supervisor, Discipline Specialist, and Editor. All text, charts, maps, photographs, and other illustrations were reviewed electronically using the Distributed Information System-II (DIS-II) and Data General workstations. Reviewer comments were added in color as an overlay using the graphics text tools.

Overall, the early electronic reviews and author revisions of text and illustrations were completed without experiencing any problems that delayed the scheduled progress of the report. The use of multiple screens to review text, illustrations, and tables is efficient; however, some enlargement features need to be utilized for smaller graphics and type fonts that are not easily visible onscreen.

The paperless report will be transferred electronically to colleague reviewers in September 1993 using the DIS-II wide-area network. Region and Headquarters reviews and Director's approval of the report are scheduled from October 1993 through January 1994. Camera-ready production and printing is scheduled to be completed by June 1994. An Open-File Report containing the documentation from this project will be compiled by the project participants.

COMPUTER-BASED, THREE-DIMENSIONAL VISUALIZATION OF OBSERVED SOLUTE DISTRIBUTIONS DURING THE CAPE COD TRACER TEST, MASSACHUSETTS

HESS, Kathryn M., *KRUGER*, Mary H., *STOCK-ALVAREZ*, E. Jessica, and *LeBLANC*, Denis R., USGS, WRD, 28 Lord Road, Suite 280, Marlborough, MA 01752

The high spatial and temporal densities of the tracer-concentration data collected during the large-scale tracer test in a sand and gravel aquifer at the U.S. Geological Survey Toxic Substances Research Site on Cape Cod, Massachusetts, make this data set ideal for testing the application of computer-based visualization to ground-water studies. Two thousand gallons of water containing the nonreactive tracer, bromide, and the reactive tracers, lithium and molybdenum (as molybdate), were injected into three closely spaced wells on July 18-19, 1985. An array of 656 multilevel samplers was installed downgradient of the injection wells. Each multilevel sampler was constructed with 15 sampling ports in the vertical direction, thus providing almost 10,000 sampling points. Approximately 57,300 samples were collected from the multilevel samplers during 19 comprehensive sampling sessions conducted during July 1985-June 1988.

The software used in this exercise is Advanced Visual Systems (AVS), which is one of the few visualization packages that run on the Data General platform. AVS creates images of spatially scattered data that can be used to explore the data in ways which would be difficult using conventional graphical techniques. For example, images can be rotated so that all sides can be viewed, isosurfaces can be peeled away to reveal the complex interior of a solute distribution, and discrete measurements of solute concentration can be spatially displayed as spheres, with the size and color of each sphere varying based on the concentration. In AVS, three-dimensional isosurfaces are constructed by interpolating between irregularly spaced data points using tetrahedrons. This algorithm results in isosurfaces that lack smoothness, but that accurately reflect the measured data. AVS also can be used to create two-dimensional slices through a three-dimensional distribution, resulting in improved versions of standard two-dimensional contour plots.

The images created by AVS visually confirm our previous understanding of the tracer-test results. Dispersion of the tracers occurred mostly in the direction of transport; dispersion transverse to flow was limited. Movement of the reactive tracers, molybdenum and lithium, was retarded and they progressively lagged behind the nonreactive bromide. Early in the test, the reactive and nonreactive tracer clouds overlapped. By making one of the images transparent in AVS, both overlapping tracer clouds can be displayed without losing the three-dimensional aspects of either one. Through this type of visualization, we gained new insight into the complexity of the tracer distributions and into the spatial and temporal relations among the three tracers.

USING A GEOGRAPHIC INFORMATION SYSTEM TO DERIVE URBAN LAND USE FROM POPULATION DATA

HITT, Kerie J., USGS, WRD, 12201 Sunrise Valley Drive, Reston, VA 22092

The National Water-Quality Assessment (NAWQA) program has developed a geographic information system (GIS) procedure to define urban land use by overlaying U.S. Bureau of the Census 1990 population density at the block group level on 1970's digital land-use data from 1:250,000- and 1:100,000-scale maps. First, the population density of the census block groups is calculated, and then the block group boundaries are overlaid on the 1970's land-use information. Any area having a population density of 1,000 or more people per square mile is re-classified as "urban" land use in the derivative map.

To evaluate the procedure, the GIS technique was applied to four NAWQA study areas. Local scientists have verified that the results give reasonable indications of urbanization that has occurred since the 1970's land-use data were compiled. The NAWQA program intends to relate water quality to urban land use in all 20 NAWQA study units. Other projects requiring up-to-date urban land use could use this technique to estimate the extent of urban land until a more current national land-use data base is compiled.

A SITE VERIFICATION PROGRAM USING ARC/INFO GEOGRAPHIC INFORMATION SYSTEM SOFTWARE

HOFFMAN, Scott A., USGS, WRD, 840 Market St., Lemoyne, PA 17043-1586

Locational errors of data points can limit their use within site-specific data bases. In particular, with the forthcoming implementation of the National Water Information System-II (NWIS-II) of the U.S. Geological Survey (USGS), verification of site-specific locations for the USGS data bases ADAPS, Ground Water Site Inventory (GWSI), WUDS, and QWDATA is a significant element. A geographic information system (GIS) can be a valuable tool for detecting latitude and longitude errors for streamflow-gaging stations, wells, water-use facilities, and water-quality data-collection sites within these data bases. A computer program has been developed in the Pennsylvania District that uses the cartographic capabilities in the Arcplot module of ARC/INFO to simplify the detection of erroneous site locations. Users may select background and foreground colors by a series of pop-up windows. Information on site-specific locations is retrieved by county or hydrologic unit by using the data-retrieval method of the particular data-base system. This information (in an ASCII file) is combined with existing USGS programs, GIS digital data sets, and on-screen display and query, to produce a file of sites with possible locational (latitude/longitude) errors. This program also could be adapted to attribute verified locations with county and hydrologic-unit data.

DEVELOPMENT OF A PLATFORM-INDEPENDENT PAPERLESS TIME AND ATTENDANCE SYSTEM

HUTTMAN, Greg, USGS, AD-OSM, 12201 Sunrise Valley Drive, Reston, VA 22092

The Administrative Division is leading a multidivision effort to develop a new Paperless Time and Attendance (T&A) system. Building on an existing system, the aim of this project is to jointly design an application capable of operating on a variety of dissimilar computers throughout the USGS—PC's, UNIX workstations, and Macs. The new system will be designed with input from all Divisions in the USGS using the Joint Application Design (JAD) approach with tools that facilitate rapid prototyping. The new system is designed to interface with the Water Resources Division Administrative Information System (AIS) and National Mapping Division's work assignment system being developed for its regional mapping centers. Elimination of the paper T&A reporting form, greatly reduced error rates, electronic routing and approval of T&A information, and more timely data entry (no need to project leave use ahead of time to meet the processing cut-off) are all achievable benefits.

Because of the use of the cross-platform application development tool, the T&A system is the first application capable of running on virtually every type of hardware, network, operating system, and database management system now in use at the USGS. A phased implementation will begin in the Administrative and Water Resources Divisions early in the summer of 1994.

THE DEVELOPMENT OF TOOLS FOR CONSTRUCTION OF INTERACTIVE INFORMATION SYSTEMS

JOHNSON, Larry E., USGS, ISD, Denver Federal Center, Box 25046, Denver, CO 80225-0046

This presentation describes the process of developing some of the necessary tools to build an interactive information system. An interactive information system is a hierarchical menu-driven system that contains and displays information in the form of hypertext documents containing pictures, graphs, sound, animation, data and meta-data. The main advantage of an interactive information system is that a user can browse through the information and skip areas that are not of interest.

This research project provides an integrated set of tools for building an interactive information system. The type of interactive information system that will be built as a result of this work is for the distribution of scientific data and information related to that data. These tools will help in the production of data sets for the sharing of data with researchers and other people who wish to gain information in a research area. The tools will make the process of producing interactive data sets on digital compact disc easier and will reduce the cost of putting the information in a usable and convenient form.

There are three major groups of end users of an Interactive Information System. The first are scientists and researchers, who will be mostly interested in the data and how to retrieve it from the digital compact disc. The second group will be decisionmakers (in industry and government), who will be interested in the results of a research project and how it will affect them. The third group will be educators, who will use the interactive information system in teaching new areas of research.

The following is a list of the tools that are being developed.

1. Tools within the interface builder
 - a. Templates for a hierarchical menu system.
 - b. Template windows to contain hypertext
 - c. Page turning facilities for large papers
 - d. Interface window for graphic files
2. Full Text Searches to find information within text fields quickly
3. Conversions for most graphic formats and resizing of graphic files

With these tools, interactive information systems can be constructed more rapidly and at a lower cost.

AUTOMATING REGRESSION AND PERFORMANCE TESTING OF NATIONAL WATER INFORMATION SYSTEM-II SOFTWARE

LENFEST, Leslie W., *BRIGGS*, John C., and *MERK*, Charles F., USGS, WRD, 12201 Sunrise Valley Drive, Reston, VA 22092

An automated software testing tool, preVue-X, is being used to support testing of the U.S. Geological Survey new storage and retrieval system for hydrologic data, the National Water Information System-II (NWIS-II). Automating testing can save time and provide an accurate and reproducible evaluation of the success of software and data-base modifications. The test tool provides support for regression and performance testing of NWIS-II. As configured for NWIS-II, preVue-X can emulate up to 16 simultaneous users performing tasks in either a designated or random pattern.

Thorough software testing during system development and maintenance consumes significant human resources. When software is modified to correct "bugs" or enhance functionality, many of the tests applied during development must be rerun after each change to ensure that errors were not introduced; this process is called regression testing.

Automated testing is initiated when preVue-X records user activities (keystrokes, and mouse movements and clicks) and system responses (including time) during a test session. Test scripts are generated from the recorded user activities and system responses at the end of the test session and can be modified to facilitate re-use and analysis of the session. Once test scripts have been prepared, they are replayed for system functional and performance analysis.

Evaluation of system responses following any software modification is accomplished by replaying scripts and utilizing preVue-X post-analysis utilities. Output from post-test analysis utilities are used by software developers to identify errors following each modification. The preVue-X graphical differencing utility is used to compare expected and actual system response from the NWIS-II user interface. Post-test analysis data are used to refine the data base and software by observing changes in performance through succeeding reruns of the test. Comprehensive testing of future versions of software can be applied indefinitely by building, updating, and maintaining the suite of recorded test sessions.

COMPREHENSIVE APPROACH TO PRODUCTION OF MAP ILLUSTRATIONS BY COMPUTER

LIEBERMANN, Timothy D., *STONE*, J. Christopher; and *PELTZ*, Lorri A., USGS, WRD, 333 W. Nye Lane, Carson City, NV 89706

The U.S. Geological Survey (USGS), Nevada District, has developed an efficient, comprehensive approach to producing map illustrations for its publications. This approach uses geographic-information-systems (GIS) technology, an extensive geospatial data base, standardized plotting macros, and an active, evolving collaboration between GIS specialists and scientific illustrators.

Methods of producing map illustrations within the USGS are changing rapidly. Geographic information systems and sophisticated graphics software are replacing manual drafting and photographic techniques. Publications staff in many USGS offices are producing printer-ready copy for complex, full-color plates. Each office—whether by design or default—has adopted its own approach, based on its local mix of personnel, expertise, inertia, available data, equipment, and software.

In the Nevada District, a structured, extensive set of geospatial data bases, referred to herein as coverages, has been assembled and is used routinely for map production. Statewide coverages include latitude/longitude graticules, geographic names, digital line graphs from 1:100,000-scale maps, and digital-elevation data (all Nevada at 1:250,000 scale and part of the State at 1:24,000 scale). Thematic coverages, such as surface geology, mines and gaging sites, also have been compiled or obtained. The base material for all digital maps is derived from this GIS “master” data base.

A plotting macro called STATE_PAGE.AML is used as a standard template for the creation of almost all map illustrations. This macro may be used for interactive display and query, production of line plots and Postscript prints, or transfer of graphics files to the scientific illustrators. The macro is an evolving set of code that reflects the collective programming expertise of the GIS staff. It also documents the location and usage of master coverages. For specific study areas or project boundaries, the macro is customized for specific map extent, scale, and projection. Project-based coverages simply are added to the macro menu. This approach eliminates effort spent on redundant programming and creation of coverages and also results in rapid production of consistent, accurate maps.

The division of labor between GIS and illustrations staff is evolving as new methods are developed and as new software becomes available. For a specific project, a GIS specialist customizes STATE_PAGE.AML and produces a series of map layers, one layer per digital file. Coverages that contain multiple plotting symbols generally are split into multiple files. A shaded relief coverage, derived from digital-elevation data, can be a useful surrogate for traditional topographic contours and is transferred in image (raster) format. Complex polygon coverages, such as surface geology, also are transferred in image format. Text, such as place names or well numbers, is transferred as nonstroked “hardware” text. The illustrator makes most decisions regarding fonts, symbology, text placement, layering of data, map rotation, and overall layout. Finished illustrations normally are sent in digital form to a commercial service bureau for conversion to high-resolution film separates. In short, the collaborators each do what they do best—the GIS specialists compile accurate digital map data, and the scientific illustrators create informative, clear maps that meet the standards for USGS publications.

A USER'S MAP OF THE DATA IN THE U.S. GEOLOGICAL SURVEY NATIONAL WATER INFORMATION SYSTEM

LOPP, Lari E., *KIRK*, James R., and *ARROYO*, Ileana E., USGS, WRD, 12201 Sunrise Valley Drive, Reston, VA 22092

The U.S. Geological Survey (USGS) second-generation National Water Information System (NWIS-II) is significantly different from NWIS-I. NWIS-I included four subsystems—ground water, surface water, water quality, and water use—and processed data on minicomputers within a distributed information system. These subsystems were logically and physically independent of one another except for one principal, shared file, the Site File. NWIS-II is an interdisciplinary system that integrates all hydrologic data and data processing for the USGS, and is designed around hydrologic features and activities. This integration in NWIS-II requires the users to change the way they physically process their data as well as how they conceptually view their data. To the user, these data may be named differently and may appear different in NWIS-II. This paper is an attempt to facilitate the user's shift from NWIS-I to NWIS-II, help clarify the complexity of data in NWIS-II, and to supplement the NWIS-II user's documentation.

The transfer of historical data from NWIS-I to NWIS-II was a complicated process; one that required an understanding of the NWIS-I rules and procedures and the NWIS-II model. In the process of defining the transfer of hydrologic data from the old to the new logical model, it was necessary to interpret and define the physical and conceptual differences of the two models and translate existing data to populate the NWIS-II data base. Two examples of the differences: First, establishing a site in NWIS-I meant describing the basic data about a site and storing the site in one record, whereas establishing a site in NWIS-II includes establishing a station, a reference location, a location offset, an event point, and the feature associated with the event point, with all of the locational data related to each other. Second, quality-assurance data in NWIS-I were logically associated with environmental data, but quality-assurance data in NWIS-II are logically and physically related to the measurements and samples. The new data and relations created during transfer are critical to maintaining the integrity of the data base with some additional data becoming mandatory in NWIS-II. To help users recognize and use their data in NWIS-II, a map has been developed that shows how the data are reorganized and related. The transfer map indicates where NWIS-I data appear in NWIS-II; how new, mandatory data elements were inferred from the NWIS-I data; how the data may have been reformatted; and what relations were built to connect conceptually related data that were structurally separate in NWIS-I. The transfer map will help the users in their transition from NWIS-I to NWIS-II.

USE OF REMOTELY SENSED DATA TO CHARACTERIZE VEGETATION IN THE RED RIVER OF THE NORTH BASIN, MINNESOTA, NORTH DAKOTA, AND SOUTH DAKOTA

LORENZ, David L., USGS, WRD, 2280 Woodale Drive, Mounds View, MN 55112

Remotely sensed data were processed by cluster analysis to evaluate vegetative cover in the Red River of the North Basin. This information provided a general classification of vegetation that was used to interpret regional water-quality data collected as a part of the National Water Quality Assessment Program of the U.S. Geological Survey.

Vegetative index data, available from the EROS Data Center of the U.S. Geological Survey, are biweekly composites of advanced very-high-resolution radiometer data from the NOAA-11 satellite. The trans-mitted data are corrected for reflectance, calibrated for receiver sensitivity, and registered to a Lambert Azimuthal Equal-Area projection. The data in the near infrared and visible bands are normalized to represent green vegetation and termed the Normalized Difference Vegetation Index.

The Normalized Difference Vegetation Index data from twelve 2-week periods (April 27 to October 11, 1990) were classified on the basis of the timing of the greenness of the vegetation through a two-step cluster analysis. In the first step, the data from each of the 259,521 pixels were put into 128 disjoint clusters. In the second step, the data from the 128 clusters were put into 13 hierarchical clusters. Visual inspection of the 13 clusters produced 8 distinct groups (4 agricultural groups, 2 water groups, 1 forested group, and 1 wetland group).

Based on the timing of vegetation greenness, three 2-week periods appeared to be critical for discerning the groups. The 2-week periods were May 25-June 7, June 8-21, and September 14-27, 1990. Classification based on these 3 periods gave sharper, better defined groups than that based on all 12 periods.

ACTIVITIES OF THE U.S. GEOLOGICAL SURVEY HYDROLOGIC ANALYSIS SUPPORT SECTION

LUMB, Alan M., USGS, WRD, 12201 Sunrise Valley Drive, Reston, VA 22092

The U.S. Geological Survey (USGS), Hydrologic Analysis Support Section (HASS), has obtained or developed, quality checked, tested, and distributed more than 40 hydrologic analysis programs to more than 90 site administrators. Specialists have been identified for each to provide software and technical support. Libraries of Fortran subroutines has been standardized and made centrally available for software developers.

To meet the full range of the USGS hydrologic processing needs and gain efficiency in meeting those needs, object-oriented design and graphical user interfaces must be well understood and appropriately used. These two technologies are being used to develop a framework for hydrologic process modeling. A process action team has been created to develop the user requirements, which have been distributed for comments, and to oversee the development of the software products.

Other needs being addressed by the HASS, in cooperation with the National Water Information System (NWIS), the Distributed Information System, and the District offices, are more efficient and effective ways to move data from NWIS to applications and to assist the Districts with software products for cooperators. One example of the latter is work with the Texas District to develop an interactive PC version of the flood-frequency program, J407, which provides tables and frequency plots for stations selected from a Texas peak-flow data file. Another example involves an interactive program that allows input of hypothetical or proposed land-use changes, translates these to surface-water model-parameter changes, runs the calibrated/validated model, the produces graphics and tables of the hydrologic effects of the land-use changes for management decisions. HASS worked with the Washington and Maryland Districts on these projects. A final example is the support provided the South Carolina and Nevada Districts for further development and support of the Real-Time Mapping (RTMAP) software.

USE OF CONDITIONAL TEXT AND HYPERTEXT IN THE USER'S MANUAL FOR THE U.S. GEOLOGICAL SURVEY NATIONAL WATER INFORMATION SYSTEM-II

MATHEY, Sharon B., and *BRIGGS*, John C., USGS, WRD, 12201 Sunrise Valley Drive, Reston, VA 22092

The U.S. Geological Survey is developing a National Water Information System-II (NWIS-II) that will replace the existing water-data information systems and integrate them into one system. FrameMaker, the report-processing system, is being used to develop the user's manual. Through features available on FrameMaker, one book file will provide a printed copy of the user's manual, an online hypertext help, and ASCII text for the "help" feature built into each window in the NWIS-II software. Although NWIS-II will have several releases before it is fully implemented, the same book file can be used for all releases of the software using the conditional text feature of FrameMaker.

Five types of conditional text are currently being used for the user's manual: printed and online, printed only, ASCII text, ASCII marker, and release 2. **Printed and online** prints and displays all text and graphics included in the printed, to-be-published version and the hypertext help document for NWIS-II. **Printed only** excludes graphics from the hypertext document that take a long time to display on the screen and are not necessary to include; for example, an input form that already is on the user's screen. **ASCII text** produces the text used for online help on individual windows. **ASCII marker** marks the beginning and ending of the text for online help on an individual window. **Release 2** identifies text that describes functions not included in the first release and is neither printed nor displayed in the first-release document.

The hypertext capability of FrameMaker links and displays related information on different pages or in different documents. The user selects a topic of interest from a main list by clicking on the topic with the mouse. This displays the appropriate page of the user manual on the screen as a view-only FrameMaker document. Icons on the screen allow the user to page forward or backward through the document, go back to a previous topic, go to the main list of topics, or exit the hypertext document.

Use of the conditional text feature of FrameMaker simplifies the task of keeping the user's manual up to date for multiple releases and for multiple purposes. With one document serving many uses, one edit updates what in the past would have been multiple documents. Use of conditional text and hypertext features allows the software developers to easily meet the user's requirement for online documentation.

A MICROCOMPUTER-BASED PERSONNEL SYSTEM DEMONSTRATION USING TOUCHSCREEN TECHNOLOGY

MATTHEWS, R. William, USGS, ISD, 12201 Sunrise Valley Drive, Reston, VA 22092

The U.S. Department of the Interior Automated Vacancy Announcement Distribution System, AVADS, was developed by the U.S. Geological Survey (USGS), on the Amdahl mainframe computer in 1987. Subsequently, a microcomputer version was developed in 1989. Both versions are currently available around the country. TouchScreen Micro AVADS was designed in 1993 to demonstrate the convenience of using a touchscreen with a microcomputer for an administrative application. In addition, the new system highlights the advantage of migrating to the Windows environment with a TouchScreen interface.

In TouchScreen Micro AVADS, the user interface was designed to enhance the information exchange. The TouchScreen version of Micro AVADS simplifies the human/computer interface. By touching the screen, the customer selects any combination of four categories: State, Series, Grade, and/or Bureau with up to six choices for each category. The computer searches the current vacancy announcements and chooses the announcements that fit the selection criteria. The computer responds with a one-line summary for each matching vacancy announcement. Based on this information the user can select an announcement to view and then decide whether or not to print a copy. This simple method of locating vacancy announcements combined with a graphical interface (point and touch) have made TouchScreen Micro AVADS an efficient means for generating rapid responses to customer queries.

The system is being used by the USGS Personnel Office in Reston, Virginia, and by the National Park Service in Denver, Colorado. The system is also available using a mouse instead of a TouchScreen at the USGS in Denver.

AN INFORMATION-REQUEST MANAGEMENT AND ACCOUNTING SYSTEM

McFADDEN, Keith W., USGS, WRD, 3039 Amwiler Road, Suite 130, Atlanta, GA 30360-2824

The large volume of hydrologic data requests from public and private sectors received by the Georgia District of the U.S. Geological Survey prompted personnel in the District to develop an information management system to monitor and document the number of requests received, action taken to respond to requests, and costs associated with filling requests. This system, designated the Information Request Management and Accounting System (IRMA), allows entry of data elements, such as the name and organization of the requestor; type of data requested; data base searched, and the name of the individual handling the request; as well as a narrative description of the request. The system also can be used for documenting processing costs and billing and for accounting purposes. Summaries of data-request activities for the month, quarter, or year can be easily prepared using IRMA. IRMA was developed in January 1991, and as of September 1993, it has been used to monitor and document nearly 2,000 requests for information from almost 500 individuals and organizations. Since IRMA was initiated, about \$54,000 has been billed to the private sector for processing data requests. IRMA was developed using INFO software on the PRIME minicomputer. Future plans are to port IRMA to the UNIX environment on Data General workstations.

MICROLINK/FFS (FEDERAL FINANCIAL SYSTEM) FOR UNIX AND U.S. GEOLOGICAL SURVEY ADMINISTRATIVE INFORMATION SYSTEM

McKINNEY, Philip, USGS, AD-OSM, 12201 Sunrise Valley Drive, Reston, VA 22092

The need to migrate certain frequently used functions of the U.S. Department of the Interior Federal Financial System (FFS) to the desktop was recognized some time ago and had resulted in the development of a PC—or desktop—version of FFS. The advantage of this approach—fast response, local access to financial data, independence from the mainframe and intervening communication connections—made the need for a UNIX version obvious. A new enhancement to the FFS, Generic Microlink/FFS, provides this capability within the Data General DG/UX and Ingres environments. This FFS enhancement, available for the first time in April 1994, combines the financial processing capabilities of Microlink/FFS with the U.S. Geological Survey Administrative Information System (AIS), with Microlink/FFS providing the means to prepare, process and transmit expenditure transactions to the mainframe FFS.

Specifically, financial data is entered and edited by Microlink/FFS operating on the local DG server, uploaded periodically to the mainframe FFS, and processed. The results are returned, along with centrally generated financial data, to the local site for reconciliation. The result is more accurate information at all levels and closer integration of local expenditure transaction processing with the official bureau accounting system.

IMPLEMENTATION OF A UNIX-BASED INVENTORY APPLICATION AT THE ROCKY MOUNTAIN MAPPING CENTER

McKINNEY, Philip, USGS, AD-OSM, 12201 Sunrise Valley Drive, Reston, VA 22092

The Administrative and National Mapping Divisions are engaged in a joint effort to modify the Federal Financial System (FFS) Inventory Subsystem to replace the order processing and inventory management system (Distribution Sales System, DSS) used by the Rocky Mountain Mapping Center in Denver, Colorado, for sales of map and book products. The project is scheduled to be implemented in April 1994.

The application will operate in a DG/UX environment in Denver. All inventory processing (order entry, inventory management, shipping, and reporting) will be performed on the local server, with accounting data to be transferred daily to the FFS official accounting system located on the Amdahl mainframe in Reston, Virginia. The data transfer will be performed with the use of FFS Microlink software. The presentation will describe the effort to develop this major business application, integrating the U.S. Department of the Interior mainframe based accounting application with the Data General capabilities.

ADMINISTRATIVE BUSINESS PROCESS RE-ENGINEERING

McKINNEY, Philip, USGS, AD-OSM, 12201 Sunrise Valley Drive, Reston, VA 22092

Administrative systems and processes are common to all organizations, and concerns about their performance and efficiency are equally common. Business process re-engineering (BPR) is a systemic approach to radically change for the better how these common functions support program activities. The U.S. Geological Survey (USGS) has begun several pilot efforts to adopt BPR and achieve its benefits. Factors compelling change include the National Performance Review findings of widespread bureaucratic inefficiencies, the USGS Chief Financial Officers' Council recommendations for streamlining the business of administration, budget compression across the bureau, internal management concerns about possible overlapping functions and duplicative systems, and quantum improvements in information technology, which provide opportunities for drastic changes in the way work is being done.

A discussion of the BPR process and how it is being applied in the USGS will be presented: The Administrative Division is leading an effort involving all divisions to review administrative processes throughout the USGS. The goal is to make significant improvements at all levels through business process re-engineering. This project initially reviews the core administrative functions of personnel, procurement, finance, facilities, and systems management. It specially focuses on the flow of work, the flow of information, the use of information technology and application systems in the course of conducting administrative business activities, and reviews as well as associated costs, risks, organizational issues, and timeliness and quality of end products and services. The next step is to design new administrative approaches and processes, determine their cost, effect, and degree of improvement, and finally to implement a selected new process as a prototype. Following a postimplementation review of the prototype, other administrative business processes will be similarly re-engineered and implemented.

SCIENTIFIC VISUALIZATION AT FLAGSTAFF IMAGE PROCESSING FACILITY, U.S. GEOLOGICAL SURVEY: PAST, PRESENT, AND FUTURE

McMACKEN, Dennis, and *BELLISIME*, Lynda, USGS ISD, 2255 North Gemini Drive, Flagstaff, AZ 86001

The term Scientific Visualization has become prominent recently in the jargon of the computer industry, but the U.S. Geological Survey, Flagstaff Image Processing Facility, has been exploring this technology for more than 20 years. The Flagstaff Image Processing Facility is a cross-divisional group. This paper presents the history, current capabilities, and future plans for Scientific Visualization at the Flagstaff Image Processing Facility.

The Flagstaff Image Processing Facility had its beginnings in the early 1970's. Early efforts were in the processing of Mariner and Viking Orbiter images in support of the Viking mission to Mars. Since that time computer scientists have worked with planetary scientists to develop specialized algorithms to get the maximum information from spacecraft images and other scientific data sets. One of the techniques pioneered in Flagstaff produces simulated true color from spectrally limited image data sets. Another program developed at Flagstaff creates shaded relief images from digital elevation model data. Throughout, one of the hallmarks is the emphasis on cartographic accuracy.

One major project involves producing image mosaics for atlases of the ocean floor using Gloria sonar data. Another prominent effort is to design and provide software tools for the widespread distribution of Viking and Voyager raw data images on CD-ROM. Part of the team is developing a map modernization package using digital methods to speed the process of getting geologic maps from the scientist into print. Another project creates CD-ROM's of image data so that teachers in schools on the Navajo-Hopi Indian reservations can introduce digital technology and stimulate student interest in Earth sciences. Flagstaff produces Landsat image maps on request for regions such as Antarctica. Flagstaff also continues to support planetary programs, such as Magellan, Voyager, Galileo, Clementine, and so forth. A sophisticated hardware and software image-display system assists users in producing the best in image processing products.

The goal for the future at the facility is to provide the user with a package of sophisticated tools that will run on UNIX workstations. A Scientific Visualization Lab will provide an advanced environment for the development, experimentation, and use of visualization software. The available software will include commercial packages, public domain software, for example, Khoros, and programs developed in-house as part of the Integrated Software for Imaging Spectrometer (ISIS) system. Lab users will be able to manipulate data to produce images and mosaics for map production and presentation graphics. Under development is a prototype of a specialized display system, which will run in a generic X-windows environment. Animation software and hardware will allow users to analyze geologic and geographic data in which change over time is an important factor.

A CENTRALIZED CONFIGURATION MANAGEMENT BOARD IN THE U.S. GEOLOGICAL SURVEY

MERK, Charles F., and *FLYNN*, Kathleen M., USGS, WRD, 12201 Sunrise Valley Drive, Reston, VA 22092

Organization and control of hardware, software, and documentation can be achieved within the U.S. Geological Survey by implementing a configuration management process and a Centralized Configuration Management Board (CCMB). Configuration Management (CM) is a baseline management system that can provide managers control of the phases of design, development, testing, review, and system integration for the production and maintenance of software and hardware systems. Within each of these phases and throughout the life cycles of the software and hardware, there will always exist the need to make changes and enhancements.

The USGS has groups that produce software for Water Resources Division (WRD) use and groups that support the platforms and networks on which this software operates. The major groups identified within the WRD are: the Distributed Information System, which includes the Applications Assistance Unit and the System Programming Unit; the Hydrologic Instrumentation Facility; the Administrative Information System; the Hydrologic Analysis Support Section; the National Water Information System; and the National Water Quality Laboratory. Changes that affect only the software and users within the individual groups would be handled by CM processes within the control of the individual group. Each of these groups should have a configuration management plan, a configuration manager, and a Configuration Management Board (CMB).

Changes or enhancements that affect more than one individual group will need to be centrally managed at a higher level. A CCMB would be formed to address issues of common concern, such as the operating system, coordinated release schedules, shared data tables, data exchange formats, and shared applications. The CCMB will consist of a regional hydrologist, a regional computer specialist, an area hydrologist or district chief, a district administrative officer, a data chief, a studies chief, a thrust project chief, a site or data-base administrator, and a district or national research program programmer. The manager of each CMB will facilitate communication among the CMB's and the CCMB and act as a technical resource to the CCMB. The CCMB will forward recommendations for changes that affect policy or require changes in resource allocations to the WRD Senior Staff. Appeals of CCMB decisions will be compiled and submitted for consideration at regularly scheduled Senior Staff meetings.

SLIDE MAKING IN A MULTIPLATFORM ENVIRONMENT

MIRZAD, S.H., and DANSKIN, W.R., USGS, WRD, 5735 Kearny Villa Road, San Diego, CA 92123

Selected hardware and software for making slides from the MS-DOS, MacOS, and UNIX platforms were evaluated by the San Diego office of the U.S. Geological Survey.

In 1988, in-house slide-making capabilities were procured to aid project personnel in rapidly producing inexpensive slides. In contrast to using an outside film laboratory, the in-house capability—using a Montage FR1 film recorder developed by Presentation Technologies—encouraged easy revisions and facilitated creation of a slide presentation in 1 to 2 days, even over a weekend. As computer equipment diversified, it became necessary to enhance the interaction of the film recorder with the MS-DOS, MacOS, and UNIX platforms and with the ethernet network.

The initial configuration of the film recorder required a parallel connection to a single MS-DOS machine. Later, a SCSI port was added to the film recorder so that a single Macintosh IIfx computer also could be used to process slides. Images from both the MS-DOS PC and Macintosh platforms were processed with relative ease, but only from the respective computers directly connected to the film recorder. No networking capability was present. Images created on the UNIX Data General environment were saved as postscript files, downloaded via the network onto the MS-DOS computer, and sent out the parallel port to the film recorder.

Advanced slide-making equipment was investigated in order to improve slide-making capability on all three platforms (MS-DOS, MacOS, and UNIX) and to take advantage of the ethernet network. The goal was to find a way to use the slide maker from multiple machines without changing cables, transferring floppy disks, or becoming overly frustrated at the logistics.

A product called SlideScript, which met these criteria, was procured and evaluated. The device essentially is a postscript interpreter. It interprets the postscript file from each of the three platforms, and translates it into the native language of the FR1 Montage film recorder, and turns the FR1 Montage into a simple postscript printer.

Postscript is a page-description language designed to communicate a description of a printable document from a computer to a raster output printing device. Because Postscript language is independent of any specific software or output devices, it can provide input to any output device that has a postscript interpreter. The SlideScript receives the postscript information and generates three high resolution images (red, green, and blue components) that the film recorder recombines to produce a full color slide. The final resolution is 4,000 lines per inch (lpi), which is sufficiently dense to obtain service-laboratory-quality slides; for comparison, the resolution is about 70 lpi on a video screen, and 300 to 600 lpi on a laser printer.

The SlideScript was connected to the MS-DOS PC's parallel port by means of a standard centronics parallel cable, to the Macintosh by an AppleTalk LocalTalk connector, and to the Data General (Aviiion 6220) server's RS-232 serial port by a straight cable. The serial port provides baud rates ranging from 2400 to 19200, although no improvement in processing time was noticed using either the 9600 or 19200 rates. Transfer time seems to be negligible in comparison with processing time for complicated slides.

The SlideScript doesn't have its own spooling utility; rather it uses the queuing system of the host computer. SlideScript polls its ports (parallel, AppleTalk, and serial) and services on a first-come, first-served basis.

Processing of postscript and encapsulated postscript files was tested successfully from MS-DOS, MacOS, and UNIX platforms using a variety of software applications. The processing time depends on the complexity of the slide as well as on the software application and computer generating the postscript file. Most slides took about 5 minutes (for simple charts) to about 20 minutes (for fairly complicated drawings). Targa high-resolution raster images were tested, but each required at least 15 minutes to process. Dumping of the screen image in X-Windowing environment on the Data General UNIX was tested; but for some unknown reason, the processing was very slow—some slides taking hours to process.

The quality of slides in most cases was similar to that obtained from a slide-service laboratory. Additional testing is being done in an attempt to correct two remaining problems. First, some slides created using Adobe Illustrator software on a Macintosh have either poor resolution of highlighted text or a poor color match with slides processed by a service-laboratory. Second, an image that fills the entire slide can be difficult to produce from some software. The underlying reason for this problem seems to be that some software recognize the SlideScript device as a postscript printer. Therefore, some scaling is required because the dimension of a printer page typically is 8.5 by 11 inches, whereas a slide image is 1 by 1.5 inches. This scaling can be cumbersome, depending on the sophistication of the software generating the postscript file. Despite these unresolved problems, the San Diego office is routinely using the device for rapid creation of slides from multiple platforms and software applications.

Cost of the system varies with the type of hardware used, but a total investment of about \$15,000 is needed for the multiple-platform slide-making equipment described above. A SlideScript Turbo, 25 MHz AMD RISC processor, 22MB RAM, and 42MB hard disk costs about \$7,000; a Montage FR2 Desktop Film Recorder (the faster, newer model) costs about \$7,000; and miscellaneous hardware items may cost a few hundred dollars.

GEONET II INTERNET ROUTING

MURPHY, Patrick, W., USGS, ISD, 275 Middlefield Road, Menlo Park, California 94025

The U.S. Geological Survey (USGS) maintains a wide-area telecommunications network known as GEONET. In April 1993, with the award of a new telecommunications contract, GEONET II, the second generation wide-area network, began to take full form. Initially six new nodes were added to the backbone of GEONET, and were integrated with dozens of existing nodes from old GEONET, forming a heterogeneous mixture of networking devices and hosts, relying on a marriage of old GEONET I and GEONET II transports. Over today's GEONET II, a complex integration of networking protocols traverse various transport layers over diverse networking hardware platforms. The old GEONET I mainstay transport, X.25, is yesterday's technology, but still has its place in this new era. Complex networking devices called routers integrate multiple protocols such as Internet Protocol (IP), Government Open Systems Interconnect Profile (GOSIP), Novell Internet Protocol Exchange (IPX), AppleTalk, and Banyon Vines with standards based transports, such as frame relay, X.25, and point-to-point protocol (PPP), supporting high speed connectivity between the USGS sites.

The new GEONET II interfaces with the new global Internet at numerous sites, such as Menlo Park, California, Denver, Colorado, Reston, Virginia, and Sioux Falls, South Dakota, at T1 speeds and greater. The sheer number and size of the new GEONET II/Internet topology create the potential for complex and interesting anomalies requiring sophisticated and intricate management tools. Configuration of these links utilize the integration of new standards based routing algorithms based on link state concepts, such as the Open Shortest Path First (OSPF), and Intermediate System to Intermediate System (IS-IS) routing protocols. These protocols converge quickly following topological changes in the network, are stable, and use very little bandwidth to effect efficient routing. A blend of old standbys, such as static routes, Routing Internal Protocol (RIP), and Exterior Gateway Protocols (EGP), as well as vendor specific interior gateway routing protocols, mix to provide the road maps that guide this intricate web, allowing networking packets to find connectionless routes to their final destinations.

The recipe that glues GEONET II together, including variable length subnet addressing, the distribution of the IP network numbers, and the interworkings of OSPF and how it interacts with other routing protocols like RIP, are the foci of this talk. The concepts of link state routing protocols and distance/vector based protocols like RIP will be compared along with a short discussion of the advantages and disadvantages of both. The GEONET II topology, past, present, and future will be summarized, and the integration of the GEONET II address space into this topology will be presented. The concept of default network will be introduced and discussed in terms of global Internet routing.

The talk will conclude with some thoughts on the much discussed topic, "What is the future of IP," and how the USGS is positioned to deal with the changing Internet, necessitated by the predicted exhaustion of the IP address space in the next 5 years.

DIGITAL MAPPING OF THE NATIONAL RIVERS INVENTORY

MURTAUGH, Peter H., USGS. NMD, 12201 Sunrise Valley Drive, Reston, VA 22092

The National Wild and Scenic River System was created by Congress in 1968 (Public Law 90-542) to preserve rivers with outstanding natural, cultural, or recreational features. Approximately 153 river segments are included in the system. In addition, there are 2,600 candidates for inclusion in the system. The National Mapping Division, U.S. Geological Survey, has developed a national rivers inventory called the river reach data base on a geographic information system to digitally manage and identify these candidates. A descriptive name, field attributes, hydrologic unit codes, and basin data were merged and tagged to the river segments creating a digital spatial product with corresponding attribute data. An interactive process identifies the extent of each file with its name, administrative area, outstanding qualities and values, and related basin data. The river reach data base uses an ARC/INFO coverage as the primary base map, overlain by the Public Lands Survey System and Federal lands boundary coverages. The combination of spatial data with river attributes make the river reach data base widely applicable, especially in the National Park Service, the Bureau of Land Management, and the Forest Service. Rivers targeted for protective measures [including one-quarter mile (just over 400 meters) on each side of the river] can be easily identified in the data base. Hydrologic attribute information obtained from this data base will assist biological research by providing a link to related field data tables and by supplying qualitative information for modeling.

USE OF WIDE-AREA INFORMATION SERVER SOFTWARE TO SUPPORT THE NATIONAL GEOSPATIAL DATA CLEARINGHOUSE

NEBERT, Douglas D., USGS, WRD, 12201 Sunrise Valley Drive, Reston, VA 22092

The Federal Geographic Data Committee (FGDC) created a Clearinghouse Working Group in 1992 to develop an on-line inventory of digital spatial data held by the Federal Government and other interested organizations. Rather than create a centralized warehouse for data, the working group is pursuing a distributed approach to data access by creating and populating a distributed, on-line inventory system. The goals of the working group are to establish telecommunications network connectivity between participants, identify digital spatial data sets, document the quality, geographic coverage, and content of the data sets, and to make this information available to all other participants. The U.S. Geological Survey has been experimenting with on-line spatial data discovery and retrieval services using a spatially enhanced public-domain version of the Wide-Area Information Server (WAIS) software to disseminate digital spatial data useful to regional or national hydrologic investigations. This software was selected by the FGDC for use in a proof-of-concept test which began in July 1993. The proof-of-concept test evaluation provides user comments on the WAIS indexing process, the client interface, and the spatial data documentation—metadata—standard guideline proposed by the FGDC to handle the information provided through the WAIS server.

THE USE OF COMPACT DISC-READ ONLY MEMORY (CD-ROM) FOR THE STORAGE OF DATA AND RELATED PROGRAMS FOR UNIX COMPUTER OPERATING SYSTEMS

NEGRI, Mark, USGS, WRD, 12201 Sunrise Valley Drive, Reston, VA 22092

With ever increasing demands for data and program storage space on magnetic disk, the need exists for an alternative means of storage. Recent developments in Compact Disc-Read Only Memory (CD-ROM) technology have made data and program storage possible on CD-ROM for use on UNIX computer operating system platforms. It is now cost effective to copy a UNIX file-system image to a CD-ROM using a stand alone write-once CD recording system. Unfortunately, Disc Operating System (DOS) limitations of eight-character file names are incorporated into the International Standards Organization (ISO) 9660 CD standard and does not fully support UNIX file names. UNIX applications using file names longer than eight-characters require the creation of a UNIX compatible "non-standard" CD. With a standard CD, data and program access speeds through a CD-ROM reader have been relatively slow compared to other means of access, such as off magnetic disk, because of the driver software. If a non-standard CD, with a UNIX file-system image on it, is mounted as a read only magnetic disk, the CD-ROM driver is bypassed making data and program access speeds comparable to access speeds directly off magnetic disk. However, a non-standard CD is not desirable for archiving purposes because the media could well outlast the ability to read it. This development in data access technology makes it feasible to distribute data or software in native UNIX format on CD-ROM.

IMPLEMENTATION OF THE U.S. DEPARTMENT OF THE INTERIOR ELECTRONIC ACQUISITION SYSTEM (IDEAS)

PALMQUIST, Donald A., USGS, AD-OPC, 12201 Sunrise Valley Drive, Reston, VA 22092, Reston, VA 22092

The U.S. Geological Survey will be the first U.S. Department of the Interior (DOI) bureau to implement the Interior Department Electronic Acquisition System (IDEAS). Although IDEAS will initially affect the internal operations of the Administrative Division procurement offices, it will ultimately reach throughout the organization. The effect of IDEAS will include everything from electronic requisitioning to status reporting to improved contract closeout.

IDEAS provides a more efficient means of operating, managing, and reporting on the procurement process in the DOI by establishing a standard, Department-wide acquisition support system capable of: permitting data entry at the source, thereby eliminating input and processing redundancies; automating the generation of requisition, solicitation, contract, and related procurement documents; actively tracking events from the beginning of a procurement to its closeout; and exchanging procurement information with the Department's financial and other administrative systems.

An overview of IDEAS features and capabilities, as well as progress towards IDEAS implementation with the U.S. Geological Survey, will be presented.

AUTOMOUNTING DAEMON PROGRAM

PRICE, Ken C., USGS, WRD, National Water Quality Laboratory, 5293 Ward Road, Arvada, CO 80002; and **TOWNSEND**, Scott, USGS, WRD, Bldg. 53, Denver Federal Center, Lakewood, CO 80225

The intent of this paper is to give an overview of the Automounting Daemon (AMD) program and present techniques for its installation and management. An automounter makes it easier to manage networks that use the Network File System (NFS) protocol.

Automounter runs as a UNIX daemon (background) process that mounts a file system whenever a file or directory within that system is referenced, and unmounts the file system after a pre-defined period of inactivity (5 minutes by default). The daemon monitors attempts to access directories that are associated with an automount map. When a user references a directory defined in an automount map, the AMD program mounts the appropriate file system for that directory.

The AMD program was developed at the London Imperial College of Science, Technology and Medicine, in conjunction with the University of California at Berkeley. It has two features that give it an advantage over traditional file system automount programs. First, the AMD program allows software-related file systems and directories to be duplicated and to have these duplicate file systems on backup software servers. As a result, if the main software server crashes, a backup server automatically will be mounted after a 5-minute delay. Thus, users only have a 5-minute wait for software to be re-served to their workstations. Second, the AMD program reduces the number of NFS file-system requests over the local network, improving network performance.

AN APPLICATION FOR THE GRAPHICAL EDITING AND ANALYSIS OF HYDROLOGIC DATA

RAEL, Patrick M., USGS, WRD, 700 West Capitol Avenue, Little Rock, AR 72201; and
TRAPANESE, Susan M., USGS, WRD, 12201 Sunrise Valley Drive, Reston, VA 22092

The U.S. Geological Survey is developing a second-generation National Water Information System (NWIS-II) that will provide the functionality of current systems plus more sophisticated software applications to manage and analyze hydrologic data. One of these applications is HYDRA, an interactive application for graphically editing and analyzing hydrologic time-series data. The development of HYDRA originated from the NWIS-II requirements specification and continues to evolve through prototyping and reviews with user groups. HYDRA, which has been written utilizing Motif and the X-Window System libraries, will be available as an integrated application in the second release of NWIS-II.

HYDRA utilizes multiwindowing capabilities to display data curves in different contexts. One window allows users to display and edit up to 10 sets of time-series values as individual curves plotted on the same graph. From this window, the user can select part of the graph to enlarge in the zoom window. This zoom window allows users to see the data curves in more detail, which allows more accurate editing of the data points and curve segments using the mouse. Another window provides a tabular listing of the data points for a selected curve and allows for some simple editing of the values using the keyboard and mouse.

HYDRA provides estimating capabilities through hydrographic and climatic data curve comparisons. Each curve is obtained from user-specified selections of constituent time-series data from the NWIS-II data base. Once the data curve has been defined by selecting the study site location and constituent to be edited, users can select additional constituents at the same location or other locations to display as support data curves. Any of the support curves can be used as a template to reshape or fill in missing periods in the data curve by moving the support curves in a manner similar to overlaying individual graphs on a light-table. Parts of a support curve can be copied into a data curve to fill in missing data. Finally, HYDRA provides visual and numeric comparisons of data for verification and quality assurance. Additional measurement data, miscellaneous observations, and threshold values can be displayed and used to check for possible erroneous values in the data curve. Once the study site curve has been edited, the revised data can be stored in the NWIS-II data base.

GUIDELINES FOR CREATING USER DOCUMENTATION FOR SOFTWARE IN THE U.S. GEOLOGICAL SURVEY

REGAN, R.S., USGS, WRD, 12201 Sunrise Valley Drive, Reston, VA 22092

User documentation for software shows how the software functions from the user's viewpoint. Key elements of the documentation describe what the software does, how it works, how to use it, how to enter and edit data, how to avoid common problems, and how to review and judge the results. The purpose of user documentation is to (1) enhance usability and (2) provide quality assurance and accountability for the software. Successful documentation presents this information in a well-organized, concise, easily understood format.

As part of the U.S. Geological Survey effort to implement Total Quality Management concepts in accomplishing its mission—to provide geologic, topographic, and hydrologic information needed for the wise management of the Nation's natural resources and for the benefit of the public—the Water Resources Division has established a Process Action Team on Software Documentation to define the process for creating successful user documentation. This document will present guidelines for the design, preparation, review, distribution, and maintenance of user documentation, with the goal of introducing standard methodologies and processes to improve and promote more consistent user documentation of software in the Water Resources Division. The user documents include Software Summary Sheet, Installation Manual, Tutorial, User Guide, Quick Reference Guide, System/Programmers Manual, and Reference Manual.

COMPUTER NETWORKING OF U.S. GEOLOGICAL SURVEY FIELD OFFICES IN THE DIS-II ENVIRONMENT AS AN ALTERNATIVE TO LEASED COMMUNICATION LINES

ROGERS, David W., and *SWEAT*, Michael J., USGS, WRD, 6520 Mercantile Way, Suite 5, Lansing, MI 48911-5971

The U.S. Geological Survey, Michigan Wide Area Network (WAN) integrated 20 workstations of the Lansing District Office Local Area Network (LAN) with the Grayling and Escanaba Field Offices, each consisting of a two workstation LAN. As a means of connecting the Grayling and Escanaba LAN's to the Michigan District WAN, Nethoppers modem/routers were installed instead of dedicated phone lines and a router. This connection reduced operating expenses because the Nethopper uses telephone services only when needed to connect to the outside world, or when information comes to a field office LAN from the outside world.

One Nethopper is required on each end of a telephone line; therefore, two Nethoppers are used in Lansing and one is used in both Grayling and Escanaba. The Nethopper requires use of one telephone line in each office. Each Nethopper has one 3.5-inch floppy drive and can be programmed by direct connection to a personal computer or dumb terminal. The Nethopper can be programmed to time out and to terminate the telephone connection after a set interval if no data transmission has occurred. Once the Nethopper is configured and running properly, virtually no maintenance is needed.

Nethoppers have been an effective means of connecting our field offices to the Internet at a cost lower than that of dedicated telephone lines. Annual cost of a dedicated telephone line between a field office and the District Office in fiscal year 1993 was quoted as \$15,000. Actual cost of two Nethoppers in fiscal year 1993 was \$3,590, and FTS telephone line charges averaged about \$200 per month, for a first year cost of \$5,990. Net savings for a first-year installation will be about \$9,010; savings in future years are estimated to be about \$13,600 per year less maintenance costs associated with the Nethopper.

DATA-BASE LOGGING AND JOURNALING SYSTEMS

SCHLESINGER, Mark J., USGS, WRD, 375 S. Euclid Avenue, Tucson, AZ 85719

The U.S. Geological Survey has developed several new applications using the INGRES data-base management system to control the storage of data. Among these applications are the Administrative Information System (AIS) and the National Water Information System-II (NWIS-II). Because many system administrators are unfamiliar with the INGRES system, corruption, recovery, and verification of data has become a concern. An understanding of the INGRES logging and journaling systems is helpful in relieving unnecessary worries about the integrity of the data stored.

The logging system uses a file to keep track of all open transactions, which allows rollbacks (removal of unwanted transactions) when needed. Knowledge of key parameters in the logging system can help with possible problems that may arise. The parameters include consistency points, log-file buffers, log-full limit, and force-abort limit. Modifications to these parameters without an understanding of what they control can lead to more problems than they will solve.

The journaling system uses a set of files to keep a record of all completed transactions. The journaling system is used when it is necessary to restore data added since the last backup of the system. Key concepts in the journaling system include when does journaling occur, the difference between table and data-base journaling, and how to use the journal to aid in data-base recovery and integrity.

Additional concepts to be considered include controlling integrity and reducing data loss in case of emergency. The issues involved are the number of buffers the logging system should keep, what size to make the log file, what is a consistency point and how does it effect both logging and journaling, and the difference between raw and regular log files. With proper care and knowledge, data-base maintenance and recovery is easy to manage.

INGRES PERFORMANCE ISSUES INVOLVING THE LOGGING AND LOCKING SYSTEMS

SHANK, Gregory L., USGS, WRD, 840 Market Street, Lemoyne, PA 17043-1586

The issue of performance has become increasingly important with the distribution of the Administrative Information System (AIS) and the National Water Information System-II (NWIS-II). Both use Ingres as their data-base management system. A discussion of the Ingres logging and locking parameters and their relation to system performance will help system administrators better understand how Ingres works within the DIS-II environment.

The Ingres system configuration can be customized in numerous ways, so it is extremely important to understand the ramifications of modifying the configuration files. The Ingres logging and locking systems parameters are defined in the file `$II_SYSTEM/ingres/files/rcp.par` (where `II_SYSTEM` is typically set to `/usr/opt`). This file contains values for 13 logging and locking parameters, 8 of which pertain to the logging system and 5 of which pertain to the locking system.

The logging parameters that have an immediate effect on system performance when changed are: (1) the transfer block size, (2) the number of log buffers in shared memory, (3) the percentage of the log to be used for consistency points, and (4) the number of consistency points taken before invoking the archiver. The locking parameters that can effect performance when altered are (1) the number of locks per transaction, and (2) the size of the locks hash table.

INCORPORATING ELECTRONIC MAPS INTO U.S. GEOLOGICAL SURVEY REPORTS

SIWIEC, Steven F., and *SOUTHERS*, Kim L., USGS, WRD, 840 Market St., Lemoyne, PA 17043-1586

Recent advances in two areas of computer technology—electronic reports processing (ERP) and geographic information systems (GIS)—have dramatically affected the way in which many U.S. Geological Survey (USGS) employees do their jobs. ERP technology has all but replaced typewriters and word processors as the standard report-processing tool in the USGS, allowing authors and report specialists to create professional reports that integrate text, graphics, tables, and mathematical formulas into a single electronic document. Sophisticated GIS tools now allow USGS scientists and engineers to conduct complex spatial analyses of their data and display a variety of geographic information with high-quality cartographic products. The recent emergence of GIS as a viable cartographic production tool has virtually eliminated the need for the time-consuming process of manual drafting of maps for USGS reports. Because of the analytical capabilities of GIS, the number and frequency of maps being developed for publication within USGS reports is increasing as the use of GIS technology increases.

In 1990, FrameMaker, an ERP package from Frame Technology Corporation, was procured as part of the Distributed Information System-II (DIS-II) contract procurement. More recently, a new GIS contract (GIS-II) has been signed with Environmental Systems Research Institute, Inc., for the ARC/INFO GIS software package. Both of these new software tools are now widely used in USGS offices nationwide. As a result, a need has developed to integrate these tools and incorporate electronic maps from GIS into reports to further automate and streamline the report preparation and publication process. This integration has been made possible recently, through use of the binary Computer Graphics Metafile (CGM), an industry-standard graphics file format that is supported by both FrameMaker and ARC/INFO.

A step-by-step procedure has been developed in the Pennsylvania District by which electronic maps are created with the ARC/INFO GIS software, exported into binary CGM format, and imported into FrameMaker to become report figures. Once maps are in FrameMaker, some editing is possible, such as the addition of text annotation or graphical objects, and scaling and positioning of the map on the physical page, using FrameMaker graphical editing tools. If it is known in advance that an electronic map is destined for FrameMaker, it is important to give consideration to the drawing order, grouping, annotation, and symbology of cartographic map elements, as these characteristics determine the degree of editing that is possible in FrameMaker.

STATISTICAL AND GEOGRAPHIC INFORMATION SYSTEM ANALYSIS OF EARTH-SCIENCE INFORMATION FOR DECISIONMAKING

SOLLER, David R., and *BERNKNOPF*, Richard L., USGS, GD, 12201 Sunrise Valley Drive, Reston, VA 22092

Societal decisions on issues, such as the siting of public facilities, are based on political and economic considerations, and are commonly supported by environmental and natural hazard information provided in map form. Because geographic information system (GIS) technology allows spatial display and analysis of various map data sets, it can be used as a tool to support the decisionmaking process. However, in support of this process, analytical capabilities of GIS are limited to spatial query (for example, distance to a feature or between features) and rudimentary statistical analysis.

Many authors have noted that current GIS software does not allow for true spatial statistical analysis. In certain applications, this limitation may not be serious—for example, if map data are available only in qualitative form, and if a regulation stipulates that urban areas underlain by a specific highly permeable geologic material be excluded from consideration for siting a landfill, then traditional GIS overlay techniques are application. If, however, a mathematical probability of slope failure due to earthquake shaking is needed to evaluate the efficiency of an earthquake mitigation strategy for a community, new techniques that rely on quantitative map attributes are needed. These new techniques form part of a fundamentally new approach that integrates traditional GIS data management, spatial analysis, and display capabilities with advanced spatial statistical methods. The advanced analytical techniques include statistical testing of multivariate data (for example, using qualitative choice regression analysis), calculation of spatial autocorrelation and its use as a guide to sample selection and grid cell size, estimation of statistical uncertainty of data, and testing for similarity of data sets (for example, through statistical comparison of means and variances).

The U.S. Geological Survey has developed analytical GIS techniques that perform the statistical functions mentioned above to support research on the utility of geologic map data in an economic decision framework. The basis for the research involves estimating the probability of occurrence of a natural hazard (for example, slope failure, ground-water contamination, or earthquake-induced liquefaction). This estimate is incorporated into the decision framework that examines the economic viability of choices (for example, on where to site a waste-disposal facility) faced in a future decision (the *ex ante* approach).

These techniques rely on quantitative Earth-science information because such data can be used with a measurable level of confidence in the decision process. Qualitative measures of the same Earth-science attributes cannot. As a consequence, qualitative map information cannot be evaluated statistically in conjunction with economic information. For example, in a waste-disposal siting decision, a dollar value for environmental costs cannot be estimated from a map that rates the likelihood of ground-water contamination as low, medium, or high; this information cannot then be evaluated and compared with information for which an economic value can be estimated (such as the transportation costs associated with selection of sites located at different distances from the waste generator). Qualitative Earth-science information can serve only a limited role in such decisions, for example as a preliminary screening tool to identify those areas obviously off-limits for waste siting. Incorporating quantitative data and rigorous statistical tests into the traditional GIS framework offers the potential of a more significant role for Earth-science information in environmental and land-use decisionmaking.

This research is conducted with ARC/INFO software (versions 5.0 to 6.1) on networked UNIX-based workstations and file servers. Operating in the vector environment, all map data are intersected with a grid composed of equal-sized square polygons that retain map information in the polygon attribute file. Our methods rely on relational data-base concepts for spatial comparison of map attributes and for integration of GIS and statistical analyses. Data and cell-ID number are output from the coverage to a file, and the data are statistically analyzed by using the Shazam and Statit software packages. Statistical computations can be transferred to INFO and related to the grid coverage for further analysis or plotting. New revisions to ARC/INFO include a raster-like component, GRID, which may offer a more efficient approach for large data sets (for example, 100,000 grid cells). The vector-based approach, however, may be preferred for the initial phase of research, perhaps involving only a subset of the map area, because it seems to offer more flexible means of querying and comparing data.

COMPUTER-SCIENCE GUEST-LECTURE SERIES AT LANGSTON UNIVERSITY SPONSORED BY THE U.S. GEOLOGICAL SURVEY

STEELE, Karen S., USGS, WRD, Building 7, 202 N.W. 66 Street, Oklahoma City, OK 73116

Langston University, a historically Black university located at Langston, Oklahoma, has a computing and information science program within the Langston University Division of Business. Since 1984, Langston University has participated in the Historically Black College and University program of the U.S. Department of the Interior, which provides education, training, and funding through a combined Earth-science and computer-technology cooperative program with the U.S. Geological Survey (USGS)

USGS personnel have presented guest lectures at Langston University since 1984. The objectives of the guest-lecture series are (1) to assist Langston University in offering state-of-the-art education in the computer sciences, (2) to provide students with an opportunity to learn from and interact with skilled computer-science professionals, and (3) to develop a pool of potential future employees for part-time and full-time employment by the USGS.

Langston University students have been enthusiastic about the lectures, and, as a result, 13 university students have been hired by the USGS as part-time employees. The USGS expanded the lecture series by increasing the number of guest lectures at the university, and by inviting professionals throughout the country to participate.

DEVELOPMENT OF DIGITAL HYDROGEOLOGIC MAP SYMBOLS FOR THE U.S. GEOLOGICAL SURVEY

TAGGART, Bruce E., and **MENOYO**, Luis E., USGS, WRD, P.O. Box 4424, San Juan, PR 00936-4424

Illustrations in publications of the U.S. Geological Survey (USGS) contain many standard map symbols. These area, line, and point symbols are not presently available in a digital format in the computer graphics programs and platforms used. To meet this need, a committee, the Digital Symbolization Working Group, was established in August 1993 to develop a standard set of digital hydrogeologic area pattern, line type, and point symbols that conform to USGS technical standards. This digital library will improve the consistency and accuracy of published illustrations, whether they are page-size maps or plates. This project has been divided into three phases: hydrogeologic point symbols, area patterns, and line types. Hydrogeologic point symbols development began in August 1993, using specifications extracted from scribing templates used by the USGS in the creation of maps and plates. This graphics software library of hydrogeologic symbols is being generated in a format compatible with ARC/INFO, FrameMaker, CorelDRAW!, Adobe Illustrator, G2, and AutoCAD, as well as other computer platforms. The area pattern and line type symbols development phases began in December 1993.

REFERENCE LISTS FOR THE U.S. GEOLOGICAL SURVEY NATIONAL WATER INFORMATION SYSTEM-II

THORNBURG, Ruth E., and *SARGENT*, B. Pierre, USGS, WRD, 12201 Sunrise Valley Drive, Reston, VA 22092

The U.S. Geological Survey is designing and developing a new system to store, analyze, and display water-resources information for the Nation. This new system, the National Water Information System-II (NWIS-II) replaces the existing water information systems.

One of the many tools built into NWIS-II is a network of reference lists. A reference list consists of allowable entries for a particular data field. For example, if entering a State code, a user can select the correct code from a reference list by simply using the mouse. By selecting data from established reference lists, data are consistent and automatically verified, and online help for entering data is provided.

Approximately 250 reference lists have been incorporated in the NWIS-II design. They range from short and simple, such as permit types (for water rights, well, or drilling), to large and complex, such as hydrogeologic units, parameter sets, or taxonomic data. Reference lists are categorized into three major groups: user-defined, user-appendable, and system. The responsible parties for updating each reference list were identified by the Strategic Planning Group (the senior staff) and the National Water Information System (NWIS) Program section chiefs. Once the NWIS-II software has been fully distributed, the personnel given the authority to update the reference lists are also responsible for reviewing the lists prior to the release and distribution of the software.

The update process for the reference lists will first depend on the category of the lists. A request for a change to a system reference list is submitted to the NWIS headquarters office in Reston, Virginia, recorded, sent to the appropriate authority for approval, returned to the NWIS office for updating, and distributed with the next release of NWIS-II. If the change involves a user-defined reference list, which is maintained at the District-level, there is no authority approval needed other than the protocol established by the District office. User-appendable reference lists are initialized at the time of transfer from NWIS-I to NWIS-II using national-level data fields that have been assigned a number ranging from 1 to 10,000,000. These lists are maintained as system-level reference lists. The unused numbers within this range are reserved for future additions of system-level information, while numbers greater than 10,000,000 are available for District-level additions and are maintained as user-defined reference lists. Therefore, any changes to user-appendable reference lists will be based on the unique numbering schema and must follow the protocol of either system reference lists or user-defined reference lists, respectively.

LABORATORY ANALYTICAL DATA SYSTEM

TURNER, Sandra L., *FEIST*, Oliver J., *LEWIS*, James A., and *HUSBAND*, Richard A., USGS, WRD, National Water Quality Laboratory, 5293 Ward Road, Arvada, CO 80002

The U.S. Geological Survey National Water Quality Laboratory (NWQL) is implementing a new Laboratory Analytical Data System (LADS) in coordination with the National Water Information System (NWIS-II) and the Administrative Information System (AIS). The design of the NWIS-II data base incorporates the tables and data elements required by LADS so that the two systems can share data and applications. Several applications developed for LADS will be used by NWIS, including the following: (1) on-line NWQL Services Catalog, (2) on-line documentation of the approved methods of analysis, (3) interactive sample login and sample tracking using bar codes, (4) quality-control review of analyses in the laboratory using the same techniques as those used in the Districts, and (5) timely transmission of data reports from the NWQL to the Districts. Several applications developed for LADS will be incorporated in AIS, including (1) project planning to allow the Districts to budget for analytical requirements, (2) financial income projections at the NWQL on the basis of District estimates for analytical requirements, (3) workload planning at the NWQL on the basis of projected analytical requirements, and (4) electronic billing that will be current, accurate, and convenient. Major improvements from the previous laboratory information management system include (1) provision for storing sample quality-management information on-line with the data to which it applies, and (2) a more accurate description of sample-processing methods in the Organic Chemistry Program.

PARALLELIZATION OF A COASTAL CIRCULATION AND TRANSPORT COMPUTER MODEL

WANG, Pearl, George Mason University, Computer Sciences Department, Fairfax, VA, 22030; and
JENTER, Harry L., USGS, WRD, 12201 Sunrise Valley Drive, Reston, VA 22092

A three-dimensional, time-dependent, finite-difference hydrodynamics model of circulation in the coastal ocean is being used to study dissolved constituent transport on a variety of spatial and temporal scales. At present, a 68 x 68 x 11 model of Massachusetts Bay and Boston Harbor provides spatial resolution of 600-6,000 meters horizontally and 30 centimeters-14 meters vertically. Simulations of 18 months with a 400-second timestep take roughly 5 days to complete on an IBM RISC 6000 model 580. In order to make calculations on finer grids and over longer simulation periods without extending the length of time that runs take to complete, new techniques for solving the model equations are being explored. The most promising technique for speeding up the model at this time appears to be parallelization of the FORTRAN code. A variety of options for parallelization exist, including both the use of high performance multi-processor computers and the use of workstation clusters acting in coordination on the same program. A version of the model for a Thinking Machines Connection Machine has been implemented and tested.

APPLICATIONS OF GEOGRAPHIC INFORMATION SYSTEMS AND STATISTICS SOFTWARE TO A LARGE DATA BASE FOR PRODUCING PUBLICATION-QUALITY FIGURES

WARNER, Kelly L., **ARNOLD**, Terri L., and **NAZIMEK**, John, USGS, WRD, 102 E. Main St., 4th Floor, Urbana, IL 61801

Output files from the software ARC/INFO, STATIT, and CorelDRAW have been combined to produce publication-quality figures for a STOP format U.S. Geological Survey (USGS) Water-Resources Investigations Report. A large data base containing concentrations of 16 inorganic constituents for ground-water samples from 2,216 public-supply wells was used to develop statistical displays and maps. This large data set was processed for baseline statistics, boxplots, and bar graphs in STATIT. Computer programs were used to transfer from the USGS water-quality data base (QWDATA) directly into ARC/INFO, a geographic information system (GIS), on Data General computers. The GIS was used to develop maps of wells in which water samples had constituent concentrations exceeded regulatory limits. Boxplots, bar graphs, text of statistics information, and maps were transformed to computer graphics files and brought into CorelDRAW for producing publication-quality color figures of combined data. Problems in converting data and output to CorelDRAW were due to format and size of graphics files.

REAL-TIME MONITORING OF A HYDROLOGIC SENSOR NETWORK

WIERDA, Clark B., USGS, WRD, 700 West Capitol Avenue, Little Rock, AR 72201

Personnel of the U.S. Geological Survey maintain networks of sensors that continually monitor the opening of the gates that control flow at several lock and dam facilities on the Arkansas River in Arkansas. At each facility, the local sensor network is connected to a Data Collection Platform that continually transmits the data by satellite. The data collection is part of an ongoing project with the U.S. Army Corps of Engineers.

Flow through the gates at each lock and dam facility is controlled by the dam operators. Dam operators have not been able to use the data provided by the sensor networks, which are able to monitor gate openings to the nearest hundredth of a foot, because these data have not been available at the damsites. The dam operators have depended upon analog dials that are graduated to whole feet. Any gate openings between whole feet must be interpolated from the dial reading.

The U.S. Army Corps of Engineers want to display the sensor readings to the dam operators at each facility. The U.S. Geological Survey has developed a prototype signal intercept and display system for the Murray Lock and Dam at Little Rock, Arkansas. This system consists of a dedicated personal computer connected to the local sensor network by an interface converter. The computer is programmed to retrieve the sensor readings and to compute the individual gate openings and flows, and the total flow for the facility. The results are displayed on the computer monitor and on a remote display terminal.

U.S. DEPARTMENT OF THE INTERIOR HAZARDOUS-WASTE SITES GEOGRAPHIC INFORMATION SYSTEM

WINGARD, Norman E., USGS, WRD, 12201 Sunrise Valley Drive, Reston, VA 22092

A geographic information system (GIS) locates and identifies the toxic or hazardous waste sites listed on the U.S. Environmental Protection Agency (USEPA) docket, for which the U.S. Department of the Interior (DOI) has management responsibility. The system has been prepared for the DOI, Office of Environmental Affairs, to be used as a management tool for tracking and monitoring the locations of hazardous-waste facilities.

The centerpiece of the system is the computer projection of all DOI sites within the conterminous 48 States. A map projection can be selected to display all sites for the conterminous States, an individual State, a selected Water Resource Region, or a user-defined area of the country. Each site is identified on screen by a colored symbol, indicating the agency with management responsibility for that site. Each site can be further identified, by means of a mouse-driven pointer to produce a look-up table with site data, including the site name, location, and so forth.

To enhance the use of the hazardous-waste site information system, a series of additional topical overlays have been incorporated that provide collateral information. These additional projections show the geographic relationships to State and county boundaries, Federal land ownership, proximity to rivers, water bodies, dams and reservoirs, the locations of NASQAN stations, land use-land cover areas, CERCLA and RCRA sites, and U.S. Geological Survey surface-water sites.

The program was developed in ARC/INFO, on the Data General (DG) Aviiion Workstation. Being on this platform, it can be operated from any DG server or individual station with an ARC/INFO license.

This system was designed specifically for use as a management tool for the DOI. It is intended, however, that any Federal agency or office with ARC/INFO capabilities may make use of this system.

A COLLABORATIVE APPROACH TO ELECTRONIC REPORT PRODUCTION

WINTERSTEIN, T.A., and MILLER, R.A., USGS, WRD, 2280 Woodale Drive, Mounds View, MN 55112

The Minnesota District of the U.S. Geological Survey, in cooperation with the Minnesota Pollution Control Agency (MPCA), used a collaborative, team approach to electronically produce a data report containing 71 maps and 22 graphs within 5 months. Work on the report began in February 1993; the printed copy of the report was delivered to the cooperator on July 7, 1993. The report summarizes bedrock hydrogeology, quaternary geology and hydrogeology, geomorphic regions, soil landscape units, land use, wetlands, ecoregions, and climatic data for the 17,000-square-mile Minnesota River basin.

The Minnesota District was able to produce the report within the 5-month deadline because of three factors. First, a project team was formed. The core project team was composed of four persons: two hydrologists, a geographic information systems specialist, and later, a cartographer. Seven other persons from the District (cartographers, a word-processist, a geographer, and an editor) completed the team. The project team adopted a collaborative approach from the initial negotiations with the MPCA through final report review and project evaluation. Second, the project team and the MPCA set clear and workable objectives. Because project members were involved early in the project, they accepted responsibility for it and made a commitment to meeting its goals. Third, electronic data were accessible in readily usable forms to produce the required maps and graphs, and the District had the software (ARC/INFO, CorelDRAW, and G2) and the expertise to rapidly process these data into illustrations.

The collaborative, team approach was essential for the success of this project. Project members were committed to the success of the project, worked together to identify problems, reached consensus about decisions that affected the entire report, and had clearly defined roles and deadlines. Most importantly, each project member knew that working together was the only way the project would be completed on time.

AUTHOR INDEX

- Acosta, A.V. 1
Arnold, T.L. 56
Arroyo, I.E. 26
- Baxter, C.R. 9
Beeler, D.A. 2, 9
Bellisime, Lynda 35
Bernknopf, R.L. 50
Boldt, D.R. 3
Bonugli, R.J. 4
Bouck, Eric 5
Brady, S.J. 6
Briggs, J.C. 24, 29
Bryant, M.R. 7
Burgess, L.M. 8
- Cauler, S.J. 9
Clark, P.G. 6
Czarnecki, J.B. 10
- Danskin, W.R. 37
- Ellis, W.H., Jr. 11
- Feist, O.J. 54
Flynn, K.M. 36
Freitag, C.J. 12
Fulton, J.L. 13
- Gerlitz, C.N. 14
Gozé, M.Y. 15
Griffin, J.W. 16
- Hallam, C.A. 17
Hathaway, R.M. 18
Hess, K.M. 19
Hitt, K.J. 20
Hoffman, S.A. 21
Holland, T.W. 7
Husband, R.A. 54
Huttman, Greg 22
- Jenter, H.L. 55
Johnson, L.E. 23
Johnson, Margaret 8
- Kirk, J.R. 26
Kratz, W.J. 6
Kruger, M.H. 19
- LeBlanc, D.R. 19
Lenfest, L.W. 24
Lewis, J.A. 54
Liebermann, T.D. 25
Lopp, L.E. 26
Lorenz, D.L. 27
Lumb, A.M. 28
- Mathey, S.B. 29
Matthews, R.W. 30
McFadden, K.W. 31
McKallip, T.E. 9
McKinney, Philip 32, 33, 34
McMacken, Dennis 35
Menoyo, L.E. 52
Merk, C.F. 24, 36
Miller, R.A. 59
Mirzad, S.H. 37
Morrell, E.M. 14
Murphy, P.W. 38
Murtaugh, P.H. 39
- Nazimek, John 56
Nebert, D.D. 40
Negri, Mark 41
- O'Connor, M.J. 2
- Palmquist, D.A. 42
Peltz, L.A. 25
Price, C.V. 11
Price, K.C. 43
- Rael, P.M. 44
Regan, R.S. 45
Reinitz, T.A. 18
Rogers, D.W. 46
- Sabatini, A.A. 6
Sargent, B.P. 53
Schlesinger, M.J. 47
Shank, G.L. 48
Siwec, S.F. 49
Soller, D.R. 50
Southers, K.L. 49
Steele, K.S. 51
Stock-Alvarez, E.J. 19
Stone, J.C. 25
Sweat, M.J. 46
- Taggart, B.E. 52
Thornberg, R.E. 53
Townsend, Scott 43
Trapanese, S.M. 44
Turner, S.L. 54
- Wang, Pearl 8, 55
Warner, K.L. 56
Wierda, C.B. 57
Wingard, N.E. 58
Winterstein, T.A. 59